

DEVELOPMENT OF SPIKE TRAIN ALGORITHMS  
FOR PHYSIOTHERAPY ASSESSMENT USING  
DEEP LEARNING APPROACHES

FADILLA 'ATYKA BINTI NOR RASHID



PTTAUTHM  
PERPUSTAKAAN TUNKU TUN AMINAH

UNIVERSITI TUN HUSSEIN ONN MALAYSIA

UNIVERSITI TUN HUSSEIN ONN MALAYSIA

STATUS CONFIRMATION FOR THESIS  
DOCTOR OF PHILOSOPHY

DEVELOPMENT OF SPIKE TRAIN ALGORITHM FOR PHYSIOTHERAPY  
ASSESSMENT USING DEEP LEARNING APPROACHES

ACADEMIC SESSION: 2020/2021

I, **FADILLA 'ATYKA BINTI NOR RASHID**, agree to allow this Thesis to be kept at the Library under the following terms:

1. This Thesis is the property of the Universiti Tun Hussein Onn Malaysia.
2. The library has the right to make copies for educational purposes only.
3. The library is allowed to make copies of this Thesis for educational exchange between higher educational institutions.
4. The library is allowed to make available full text access of the digital copy via the internet by Universiti Tun Hussein Onn Malaysia in downloadable format provided that the Thesis is not subject to an embargo. Should an embargo be in place, the digital copy will only be made available as set out above once the embargo has expired.
5. \*\* Please Mark (✓)

☐

CONFIDENTIAL

(Contains information of high security or of great importance to Malaysia as STIPULATED under the OFFICIAL SECRET ACT 1972) *Title and Abstract only*

☐

RESTRICTED

(Contains restricted information as determined by the Organization/institution where research was conducted) *Title, Abstract and Introduction only*

☐

EMBARGO

until \_\_\_\_\_  
(date) (date)

☒

FREE ACCESS



(WRITER'S SIGNATURE)

Approved by,



(SUPERVISOR'S SIGNATURE)

Permanent Address:

NO 4, JALAN GEMILANG 4/10,  
TAMAN BUKIT FLORA,  
83000, BATU PAHAT JOHOR.

Date : 21/3/2021

Date: 21/3/2021

NOTE:

\*\* If this Thesis is classified as CONFIDENTIAL or RESTRICTED, please attach the letter from the relevant authority/organization stating reasons and duration for such classifications.

This thesis has been examined on date 8<sup>th</sup> February 2021  
and is sufficient in fulfilling the scope and quality for the purpose of awarding the  
Degree of Doctor of Philosophy in Electrical Engineering.

Chairperson:

ASSOC. PROF. DR. SITI ZARINA BINTI MOHD MUJI  
Faculty of Electrical and Electronic Engineering  
Universiti Tun Hussein Onn Malaysia

Assistant Chairperson:

MDM ZARINA BINTI TUKIRAN  
Faculty of Electrical and Electronic Engineering  
Universiti Tun Hussein Onn Malaysia

Examiners:

PROF. DR. NOORITAWATI BINTI MD. TAHIR  
Research Nexus UiTM (ReNeU)  
Universiti Teknologi MARA (UiTM Shah Alam)

ASSOC. PROF. IR. DR. ABD KADIR BIN MAHAMAD  
Department of Electronic Engineering  
Faculty of Electrical and Electronic Engineering  
Universiti Tun Hussein Onn Malaysia



DEVELOPMENT OF SPIKE TRAIN ALGORITHMS FOR PHYSIOTHERAPY  
ASSESSMENT USING DEEP LEARNING APPROACHES

FADILLA' ATYKA BINTI NOR RASHID


A thesis submitted in  
fulfillment of the requirement for the award of the  
Doctor of Philosophy in Electrical Engineering



Faculty of Electrical and Electronic Engineering  
Universiti Tun Hussein Onn Malaysia


FEBRUARY 2021

I hereby declare that the work in this thesis is my own except for quotations and summaries which have been duly acknowledged

Student : 

FADILLA' ATYKA BINTI NOR RASHID

Date : 21/3/2021

Supervisor : 

DR. NOR SURAYAHANI BINTI SURIANI

Co-Supervisor: 

DR. AIN BINTI NAZARI



PTTA UTHM  
PERPUSTAKAAN TUNKU TUN AMINAH

Beloved family, thank you.



## ACKNOWLEDGEMENT

Foremost, praises and thanks to God, the Almighty, for His showers of blessing for granting me wisdom and strength not only for the journey of research but indeed throughout my entire life.

I would like to express my deepest and sincere gratitude to my amazing supervisor, Dr. Nor Surayahani binti Suriani, for the opportunity and providing me invaluable guidance along with my postgraduate studies. Her patience, motivation, enthusiasm and immense knowledge were much appreciated. I could not have imagined having a better advisor and mentor than her. Thank you, Dr. I also would like to express my gratitude to my Co-Supervisor, Dr. Ain binti Nazari, for her encouragement and insightful comments in guiding me towards the betterment of the research works.

I am extremely grateful to my family for their endless supports, loves, prayers and scarifies in both emotionally and physically in preparing me for my future. Thank you, Pa, Ma, Abang.

My sincere appreciation goes to the Ministry of Higher Education Malaysia and UTHM for providing a research grant under vote FRGS 1584 that financially supported this research to completion.

I also would like to thank Dr. Mohd Norzali bin Hj Mohd for providing me with Kinect device that has been helping me a lot through the data collection phase, also thank you to Prof. Dr. Yusri bin Yusof for allowing me to have a workspace in AMMC Lab in order to complete the research works.

Last but not least, I extend my appreciation to my friends, Fareza, Anbia, Shamy, Ehsan and many others for their unwavering support and who have stood by me through so many tough times.

## ABSTRACT

Physiotherapy nowadays has become a demanding medication for curing bones related injuries and pain to restore someone's to health in order to gain back the ability to cope with daily living tasks. As the technologies of sensors have risen, smart physiotherapy monitoring systems become trendy researches due to its potential to enhance the quality of physiotherapy assessment. However, varied sensor technologies of physiotherapy assessment have lacked versatility and robustness. This research proposed a spike train feature extraction for physiotherapy assessment to enhance the patient's progression. However, the concerns are how capable is spike trains in achieving high accuracy as other related works on recognising and assessing rehabilitation movements. In this context, spike trains are defined as sequences of recorded times when neurons fire spikes or also known as action potentials. This study implemented a spike train as a primary method of feature extraction that illustrated a significant pattern for each exercise performed. Three datasets, UI-PRMD dataset, K3Da dataset, and Self-Collected dataset have been adopted in the studies to be encoded into spike trains formal representation which resulting to an average of 415 spike patterns. Next, the patterns of raster plots were being trained as the input into a deep learning framework to evaluate the accuracy of the pattern's uniqueness. Furthermore, this study makes use of the occurrence of spikes' number, which is known as firing rate, to distinguish movements' correctness and being compared with the deep learning evaluation measures to prove the efficiency of deep learning prediction. The proposed framework achieved recognition rates of 99.44%, 98.21%, and 100.00% for UI-PRMD, K3Da, and self-collected datasets, respectively. These results proved that the proposed framework achieved targetable accuracy for all datasets trained with various CNN architectures. Next, the experimental results of physiotherapy assessment indicate that the correctness prediction by the proposed framework closely follows the ground-truth value for the movements. This study is among the first successful attempts of implementing spike train into a deep learning



framework for a real-time-based rehabilitation session case study with promising results. Hence, spike train is the foremost choice as features that are hugely rewarding towards deep learning as it can visually differentiate each of the physiotherapy movements with unique patterns.



PTTA UTHM  
PERPUSTAKAAN TUNKU TUN AMINAH

## ABSTRAK

Fisioterapi kini dilihat menjadi permintaan tinggi dalam merawat kecederaan individu yang berkaitan tulang agar mereka dapat kembali melakukan rutin harian seperti individu biasa. Sejalan dengan pesatnya pembangunan penderia, sistem pemantauan fisioterapi pintar semakin giat dibangunkan kerana potensinya yang berupaya membantu keberkesanan penilaian fisioterapi. Walau bagaimanapun, ketahanan dan kepelbagaian teknologi penderia di dalam penilaian fisioterapi dilihat agak ketinggalan. Kajian ini mengutarakan pembaharuan penyarian fitur *spike train* bagi memperbaiki mutu kemajuan pesakit di dalam penilaian fisioterapi. Namun, yang menjadi kebimbangan adalah bagaimana *spike train* mampu mencapai ketepatan tinggi seperti penyelidikan yang lepas dalam mengenali dan menilai pergerakan rehabilitasi. Dalam konteks ini, *spike train* didefinisikan sebagai urutan masa yang direkod apabila lonjakan neuron meningkat atau boleh dikenalpasti sebagai potensi tindakan. Kajian ini menjadikan *spike train* sebagai kaedah utama penyarian fitur bagi memberi ilustrasi corak yang penting pada setiap ujian yang telah dilakukan. Tiga set data, data UI-PRMD, data K3Da, dan data *Self-Collected* telah dimasukkan ke dalam kajian ini dan diterjemah ke dalam wakil umum *spike train* di mana ia menjurus kepada purata corak sebanyak 415. Seterusnya, kami menganimasikan hasil corak tersebut ke dalam kerangka pembelajaran mendalam untuk mengenalpasti ketepatan corak yang unik. Tambahan pula, penggunaan bilangan lonjakan berlaku yang dikenali sebagai kadar tembakan dalam kajian ini dapat mengenalpasti ketepatan pergerakan dan dibezakan bersama ukuran penilaian pembelajaran dalaman sekaligus membuktikan kecekapan ramalan pembelajaran mendalam. Kerangka yang dicadangkan masing-masing telah berjaya mencapai kadar nilai pengiktirafan sebanyak 99.44%, 98.21% dan 100.00% untuk UI-PRMD, K3Da dan data yang dikumpulkan secara persendirian. Keputusan ini telah membuktikan bahawa set data yang dianimasikan di dalam kajian ini adalah tepat dan mengikut spesifikasi pelbagai seni bina yang disarankan CNN. Selanjutnya, keputusan eksperimen dari penilaian fisioterapi menunjukkan bahawa nilai ketepatan

ramalan daripada kerangka yang dicadangkan bertepatan dengan nilai sebenar untuk pergerakan. Kajian ini adalah antara percubaan pertama yang berjaya dalam melaksanakan *spike train* ke kerangka pembelajaran mendalam untuk kajian kes sesi pemulihan berasaskan masa nyata dengan hasil yang menjanjikan. Justeru, *spike train* adalah pilihan yang jitu sebagai ciri yang terbaik kepada pembelajaran mendalam kerana ianya sangat bermanfaat untuk membezakan visual bagi setiap pergerakan fisioterapi yang masing-masing mempunyai corak yang unik.



PTTA UTHM  
PERPUSTAKAAN TUNKU TUN AMINAH

## CONTENTS

<b>TITLE</b>	<b>i</b>
<b>DECLARATION</b>	<b>ii</b>
<b>DEDICATION</b>	<b>iii</b>
<b>ACKNOWLEDGEMENT</b>	<b>iv</b>
<b>ABSTRACT</b>	<b>v</b>
<b>ABSTRAK</b>	<b>vii</b>
<b>CONTENTS</b>	<b>ix</b>
<b>LIST OF TABLES</b>	<b>xiii</b>
<b>LIST OF FIGURES</b>	<b>xvi</b>
<b>LIST OF SYMBOLS AND ABBREVIATIONS</b>	<b>xx</b>
<b>LIST OF APPENDICES</b>	<b>xxiv</b>
<b>CHAPTER 1 INTRODUCTION</b>	<b>1</b>
1.1 Research Background	1
1.2 Problem Statement	3
1.3 Research Aim	4
1.4 Research Objectives	4
1.5 Research Scopes	5
1.6 Research Contributions	6

1.7	Thesis Outlines	7
-----	-----------------	---

## **CHAPTER 2 LITERATURE REVIEW** **8**

2.1	Introduction	8
2.2	Definition of physiotherapy	8
2.3	Physiotherapy Assessment	12
2.3.1	Conventional Physiotherapy Assessment	12
2.4	Kinect-Based Physiotherapy Assessment	14
2.5	Human Detection	18
2.5.1	Depth Maps	19
2.5.2	Skeleton Joints	22
2.6	Spike Trains Algorithm	28
2.6.1	Related Work on Spike Trains	30
2.7	Human Recognition and Classification	31
2.7.1	Related Work on Physiotherapy Recognition	31
2.8	Related Work on Physiotherapy Assessment	34
2.9	Summary	36

## **CHAPTER 3 RESEARCH METHODOLOGY** **39**

3.1	Introduction	39
3.2	Research Methodology Flowchart	40
3.3	Overview of Proposed Framework	41
3.4	Dataset	44
3.4.1	Secondary Data	44
3.4.2	Primary Data	51
3.5	Data Preparation	55
3.6	Spike Generation	57
3.6.1	Spike Train Formal Representation in Raster Plot	58
3.6.2	Tuning Curve for Average of Firing Rates	60
3.7	Deep Learning Approaches	63
3.7.1	Classification Recognition Rate	72
3.7.2	Physiotherapy Assessment	73
3.8	Summary	73



<b>CHAPTER 4 RESULTS AND DISCUSSIONS</b>	<b>75</b>
4.1 Introduction	75
4.2 Significance Patterns of Spike Train in Raster Plot	76
4.2.1 UI-PRMD Dataset Results	76
4.2.2 K3Da Dataset Results	77
4.2.3 Self-Collected Dataset Results	80
4.3 Movement Correctness by Tuning Curves of Average Firing Rate	81
4.3.1 UI-PRMD Dataset Results	82
4.3.2 K3Da Dataset Results	84
4.3.3 Self-Collected Dataset Results	90
4.4 Recognition Rate	95
4.4.1 UI-PRMD Dataset Results	97
4.4.2 K3Da Dataset Results	99
4.4.3 Self-Collected Dataset Results	101
4.5 Physiotherapy Assessment Validation	103
4.5.1 UI-PRMD Dataset Results	104
4.5.2 K3Da Dataset Results	108
4.5.3 Self-Collected Dataset Results	111
4.6 Summary	113
<b>CHAPTER 5 APPLICATION OF PROPOSED FRAMEWORK IN REHABILITATION MOVEMENT CLASSIFICATION SYSTEM (REMOC)</b>	<b>115</b>
5.1 Introduction	115
5.2 REMOC	115
5.3 Attributes of REMOC	116
5.4 User Manual for REMOC	117
5.4.1 Recording A Physiotherapy Session	118
5.4.2 Save and Stop Physiotherapy Session	119
5.4.3 Generating Spike Significant Pattern for Performed Exercises	120
5.4.4 Displaying the Classification Results of Performed Exercises	121



PTTA UTHM  
PERPUSTAKAAN TUN AMINAH

5.4.5	Displaying Progress Percentage of Performed Exercises	122
5.5	Usefulness of REMOC	123
5.6	Expert Validation on REMOC	123
5.7	User Testing Feedback	124
5.8	Summary	126
<b>CHAPTER 6</b>	<b>CONCLUSION AND RECOMMENDATION</b>	<b>127</b>
6.1	Introduction	127
6.2	Research Conclusion	127
6.3	Contribution of research	128
6.3.1	Contribution to body of knowledge	128
6.3.2	Contribution to Physiotherapy Industry	129
6.4	Recommendation for Future Works	129
<b>REFERENCES</b>		<b>131</b>
<b>APPENDICES</b>		<b>154</b>
<b>VITA</b>		<b>174</b>



PT TA UTHM  
PERPUSTAKAAN TUNKU TUN AMINAH

## LIST OF TABLES

1.1	Types of exercises correspond to the conditions	2
2.1	Experiences and conditions for a patient who seeks for physiotherapy	10
2.2	Types of physiotherapy and its explanation	11
2.3	Limitations of conventional approaches on physiotherapy assessment	15
2.4	Technical specification comparison of Kinect v1 and Kinect v2	16
2.5	Kinect depth maps features for physiotherapy assessment	21
2.6	Kinect skeleton joints type for v1 and v2	25
2.7	Kinect skeleton joint features for physiotherapy assessment	26
2.8	Limitations and research gaps for previous feature extraction methods on skeleton joint data	27
3.1	List of Exercise in UI-PRMD Dataset [216]	46
3.2	22-joints utilised by UI-PRMD dataset	48
3.3	List of Exercises in K3Da Dataset [219]	50
3.4	List of exercises in self-collected dataset	52
3.5	Details of subjects for data collection	54
3.6	Layers of a CNN architecture	65
3.7	Details of CNN architectures	66
3.8	Summary on proposed CNN architecure	69
3.9	Structure of Identity Block	70
4.1	Dataset summarization	75
4.2	Correctness metrics of an incorrect movement based on the correct movement for a subject in UI-PRMD dataset	84
4.3	Ground truth and subjects' details	84
4.4	Correctness metrics for Balance Open Eyes based on ground truth	85
4.5	Correctness metrics for Chair Stand based on ground truth	86



4.6	Correctness metrics for Maximum Jump based on ground truth	87
4.7	Correctness metrics for One Leg Balance based on ground truth	88
4.8	Correctness metrics for Walking towards Kinect based on ground truth	89
4.9	Ground truth and subjects' details	90
4.10	Correctness metrics for Squat based on ground truth	91
4.11	Correctness metrics for Lunges based on ground truth	92
4.12	Correctness metrics for Heel Raise based on ground truth	93
4.13	Correctness metrics for Sit to Stand based on ground truth	94
4.14	Correctness metrics for Leg Raise based on ground truth	95
4.15	Recognition Rate for UI-PRMD Dataset by CNN Architectures	97
4.16	Comparison of Proposed CNN and Other Approaches by Using UI-PRMD Dataset	98
4.17	Recognition rates for K3Da Dataset Exercise Classification by CNN Architectures	99
4.18	Comparison of Proposed CNN and Other Approaches by Using K3Da Dataset	101
4.19	Accuracy for Self-Collected Dataset Exercise Classification by CNN Architectures	102
4.20	Comparison of Proposed CNN and Other ML for Self-Collected Dataset	103
4.21	Correctness Metrics of UI-PRMD for 5 Subjects	105
4.22	Comparison of correctness metrics predicted by proposed CNN and other CNN models for UI-PRMD	106
4.23	Comparison of Correctness Metrics from Deep Learning Prediction and Firing Rate Calculation for UI-PRMD	107
4.24	Correctness Metrics of K3Da for 5 Subjects	108
4.25	Comparison of correctness metrics predicted by proposed CNN and other CNN models for K3Da	109
4.26	Comparison of Correctness Metrics from Deep Learning Prediction and Firing Rate Calculation for K3Da	110
4.27	Correctness Metrics of Self-collected data for 4 Subjects	111
4.28	Comparison of correctness metrics predicted by proposed CNN and other CNN models for Self-Collected Data	112



4.29	Comparison of Correctness Metrics from Deep Learning Prediction and Firing Rate Calculation for Self-Collected Data	113
5.1	Details of Usability Scale on Individual's Response	125



PTTA UTHM  
PERPUSTAKAAN TUNKU TUN AMINAH

## LIST OF FIGURES

2.1	General flow of rehabilitation session in a rehabilitation centre	14
2.2	General framework of human action recognition	17
2.3	Example of comparison between normal and depth image using Kinect v2	19
2.4	(a) 20-Joints of human body in action recognition through Kinect v1	24
2.5	Example of experiment setup on classification using spike train dissimilarities where the measure is used to quantify the dissimilarity between a new spike train and reference spike trains for each of the stimuli	29
3.1	Research flowchart	40
3.2	Comparison of methodology of current method and proposed framework for physiotherapy assessment system	42
3.3	General overview of proposed framework	43
3.4	Sample of exercises from UI-PRMD Datasets [216], referring to the list in Table 3.1	47
3.5	Environmental setup for the recording session of K3Da dataset [219]	49
3.6	Example output of K3Da dataset [219]	49
3.7	Sample of exercises by the subjects for self-collected dataset referring to the list in Table 3.3	53
3.8	Example of primary data collection setup	53
3.9	The interface of real-time data captured in MATLAB software for seated posture before starting sit-to-stand exercise	54
3.10	Diagram of the whole process in data preparation for this study	55
3.11	a) ISI-distance, an illustration of the local quantities used to define the dissimilarity profile, b) SPIKE-distance, an illustration	

	of the additional local quantities needed for the calculation of the dissimilarity profile, c) SPIKE-synchronization, an illustration of the adaptive coincidence detection [225]	59
3.12	An example of raster plot for a set of spike trains	60
3.13	Example of tuning curve	61
3.14	Neural network with an input layer, two hidden layers, and an output layer	64
3.15	Example of CNN architecture	65
3.16	CNN1 architecture [228]	66
3.17	CNN2 Architecture [229]	67
3.18	CNN3 Architecture [230]	68
3.19	CNN4 Architecture [230]	68
3.20	(a) Proposed CNN architecture, (b) Fully connected layers with 0.5 probability dropout and a softmax layer employed in proposed CNN	71
4.1	Sample patterns of spike train in raster plot for UI-PRMD dataset; a) Deep Squat, b) Hurdle Step, c) Inline Lunges, d) Sit to stand, e) Standing Shoulder Extension, f) Leg Raise	78
4.2	Sample patterns spike train in raster plot for K3Da dataset; a) Balanced Open Eyes, b) Chair Stand, c) Maximal Jump, d) One Leg Balanced Open Eyes, e) Walking towards Kinect	79
4.3	Sample patterns spike train in raster plot for Self-Collected dataset; a) Squat, b) Lunges, c) Heel Raise, d) Sit to stand, e) Leg Raise	80
4.4	Comparison average firing rates of six correct and incorrect movements for a subject	83
4.5	Comparison of Average Firing Rate of five subjects based on ground truth for Balance Open Eyes	85
4.6	Comparison of Average Firing Rate of five subjects based on ground truth for Chair Stand	86
4.7	Comparison of Average Firing Rate of five subjects based on ground truth for Maximum Jump	87
4.8	Comparison of Average Firing Rate of five subjects based on ground truth for One Leg Balance	88

4.9	Comparison of Average Firing Rate of five subjects based on ground truth for Walking towards Kinect	89
4.10	Comparison of Average Firing Rate of four subjects based on ground truth for Squat	91
4.11	Comparison of Average Firing Rate of four subjects based on ground truth for Lunges	92
4.12	Comparison of Average Firing Rate of four subjects based on ground truth for Heel Raise	93
4.13	Comparison of Average Firing Rate of four subjects based on ground truth for Sit to Stand	94
4.14	Comparison of Average Firing Rate of four subjects based on ground truth for Leg Raise	95
4.15	Overall performance of physiotherapy recognition rate	96
4.16	UI-PRMD Recognition Rate by CNN architectures	97
4.17	Confusion Matrix of recognition rate by proposed CNN for UI-PRMD dataset ( $R^R = 0.9944$ )	98
4.18	K3Da Recognition Rate by CNN architectures	99
4.19	Confusion Matrix of recognition rate by proposed CNN for K3Da dataset ( $R^R = 0.9821$ )	100
4.20	Comparison of Jump and One Leg Balance patterns	100
4.21	Self-Collected Recognition Rate by CNN architectures	102
4.22	Confusion Matrix of recognition rate by CNN3 for Self-Collected Dataset ( $R^R = 1.000$ )	102
4.23	Comparison on spike train pattern of incorrect movement and correct movement for Deep Squat performed by Subject 1	104
4.24	Physiotherapy Assessment Validation for UI-PRMD	107
4.25	Physiotherapy Assessment Validation for K3Da	110
4.26	Physiotherapy Assessment Validation for Self-Collected Dataset	113
5.1	General overview of REMOC prototype	116
5.2	Record Attributes	118
5.3	Save Attributes	119
5.4	Spike attributes	120
5.5	Classify attributes	121
5.6	Percentage Attributes	122

5.7	Expert Validation by Mr Shahari Azri, UTHM Physiotherapist	124
5.8	Usability Sclae for REMOC	124



PTTA UTHM  
PERPUSTAKAAN TUNKU TUN AMINAH

## LIST OF SYMBOLS AND ABBREVIATIONS

AAD	–	Average Absolute Deviation
AI	–	Artificial Intelligence
ADLCAP	–	Activity Daily Living Clinical Assessment Protocol
ANARX	–	Additive Nonlinear Auto-Regressive Exogenous
ANFIS	–	Adaptive Neuro-Fuzzy Inference System
ANN	–	Artificial Neural Network
BNN	–	Backpropagation Neural Network
BoS	–	Base of Support
CNN	–	Convolutional Neural Network
CMU-MMAC	–	CMU Multi-Modal Activity
CoM	–	Centre of Mass
DL	–	Deep Learning
DMM	–	Depth Motion Maps
DNN	–	Deep Neural Network
DTW	–	Dynamic Time Warping
EMG	–	Electromyographic
ERF	–	Enhanced Random Decision Forest
FMA	–	Fugl-Meyer Assessment
GPU	–	Graphic Processing Unit

GRBM	–	Gaussian Restricted Boltzmann Machines
HCI	–	Human-Computer Interaction
HMM	–	Hidden Markov Model
HNN	–	Hierarchical Neural Network
HOG	–	Histogram of Gradient
HOF	–	Histogram of Optical Flow
HOJ3D	–	Histogram of 3d Joint Locations
HON4D	–	Histogram of Oriented 4D Normal
HPTE	–	Home-based Physiotherapy Exercises
HSMM	–	Hidden Semi-Markov Model
ISMAL	–	Integrated Sports Medicine Movement Analysis Laboratory
K3Da	–	Kinect 3D active
k-NN	–	k-Nearest Neighbour
KiReS	–	Kinect Rehabilitation System
LBP	–	Local Binary Patterns
LR	–	Logistic Regression
LTDP	–	Local Ternary Direction Pattern
LTP	–	Long-Term Potentiation
MAD	–	Mean Absolute Deviation
MHAD	–	Multi-Modal Human action Dataset
ML	–	Machine Learning
MLP	–	Multilayer Perceptron
MPE	–	Mean Percentage Error





MSR	–	Microsoft Research
NARX	–	Nonlinear Auto-Regressive Exogenous
NN	–	Neural Network
PCA	–	Principle Component Analysis
PHOG	–	Pyramid of Histogram of Gradient
RBF	–	Radial Basis Function
RDF	–	Random Decision Forest
REMOC	–	Rehabilitation Movement Classification
RGB-D	–	Red Green Blue Depth
RNN	–	Recurrent Neural Network
ROI	–	Region of Interest
ROM	–	Range of Motion
RULA	–	Rapid Upper Limb Assessment Scoring
PNN	–	Probabilistic Neural Network
SDK	–	Software Development Kit
SIFT	–	Scale-Invariant Feature Transform
SNN	–	Spiking Neural Network
SPPB	–	Short Physical Performance Battery
SVM	–	Support Vector Machine
TBI	–	Traumatic Brain Injury
TUG	–	Timed Up and Go
UI-PRMD	–	University of Idaho-Physical Rehabilitation Movement Data
UTD	–	University of Dallas, Texas

VERA	–	Virtual Exercise Rehabilitation Assistant
WHO	–	World Health Organization
WMFT	–	Wolf Motor Function Test
ZVC	–	Zero-Velocity Crossing



PTTA UTHM  
PERPUSTAKAAN TUNKU TUN AMINAH

## LIST OF APPENDICES

APPENDIX	TITLE	PAGE
A	Sample of Datasets	154
B	Informed Consent and Subjects' Information Sheet for Self-Collected Dataset	157
C	Publication List	171
D	Awards List	173



PTTA UTHM  
PERPUSTAKAAN TUNKU TUN AMINAH

## CHAPTER 1

### INTRODUCTION

#### 1.1 Research Background

Physiotherapy, a part of modern healthcare, is concerned with the development, maintenance, and restoration of body movement and functionalities after illness or injury [1]. Various types of diseases and illnesses need to be cured by doing several exercises in order to manage pain and prevent diseases. Medical experts or therapists have been trained to evaluate and treat people who have movement disabilities and inabilities to perform daily tasks due to an injury or illness. Strokes, brain injuries, motor disabilities, sports injuries, post-accident injuries, and Parkinson's disease are examples of diseases that undergo physiotherapy.

Stroke, also known as cerebrovascular accident or brain attack, is one of the top five leading causes of death and one of the top 10 causes for hospitalisation in Malaysia [2]. According to the World Health Organization (WHO), stroke ranks as the second leading cause of death. Physiotherapy can help stroke patients gaining muscle control and strength back depending on the severity of the stroke. 50% of stroke survivors suffer from an impairment of motor function that requires prolonged rehabilitation [3].

Patients usually will be given exercises or training within their own pace and tolerance levels. The training that adequate for a patient may not be equally adequate for others. Several types of physical therapy exercises depend on patients' particular conditions and physical capabilities. Table 1.1 summarises the exercises together with the examples and conditions.

Table 1.1: Types of exercises correspond to the conditions

Physical Therapy Exercises	Explanation	Examples of Exercises	Conditions
Range of Motion	Range of Motion (ROM) exercises help in moving joints to prevent stiffness.	<ul style="list-style-type: none"> <li>• Active ROM</li> <li>• Passive ROM</li> <li>• Active-assisted ROM</li> </ul>	<ul style="list-style-type: none"> <li>• Arthritis</li> <li>• Sport injuries</li> <li>• Post-Surgical Healing</li> <li>• Caution</li> </ul>
Muscles Strengthening Exercises	It is increasing muscle strength to gain better balance, mobility, and ability for healthy lifestyle.	<ul style="list-style-type: none"> <li>• Squat</li> <li>• One-Arm Row</li> <li>• Modified Push-Up</li> <li>• Shoulder Press</li> <li>• Knee Extension</li> <li>• Bridging</li> <li>• Sit to Stand</li> </ul>	<ul style="list-style-type: none"> <li>• Weight control</li> <li>• Pulmonary diseases</li> <li>• Stroke</li> <li>• Heart diseases</li> </ul>
Balance Exercises	Balance exercises can help people with proper balancing or people who have muscles weakness preventing them from sudden falls.	<ul style="list-style-type: none"> <li>• Standing one foot</li> <li>• Walking in a straight line</li> <li>• Yoga, Tai Chi</li> </ul>	<ul style="list-style-type: none"> <li>• Stroke</li> <li>• Cardiac event</li> <li>• Elderly</li> <li>• Low Blood Pressure</li> </ul>
Endurance Exercises	Increase breathing and heart rate to improve the health of the lungs and heart as well as improve a person's overall fitness.	<ul style="list-style-type: none"> <li>• Waking</li> <li>• Stairs Climbing</li> </ul>	<ul style="list-style-type: none"> <li>• Parkinson's</li> <li>• Cardiovascular diseases</li> </ul>
Flexibility Exercises	Stretching can help improve the human body to become more flexible and limber.	<ul style="list-style-type: none"> <li>• Hamstring Stretch</li> <li>• Chest Stretch</li> <li>• Calf Stretch</li> <li>• Back Stretch</li> <li>• Shoulder Stretch</li> <li>•</li> </ul>	<ul style="list-style-type: none"> <li>• Back pain</li> <li>• Disc Diseases</li> <li>• Parkinson's</li> </ul>
Post-Surgery Exercises	Surgery patients experienced pain, muscle contractions, and stiffness. Physical therapy can relieve these issues by gradually adjusting the physical conditioning	<ul style="list-style-type: none"> <li>• Head Lift</li> <li>• Buttock Lift</li> <li>• Walking</li> </ul>	<ul style="list-style-type: none"> <li>• Depends on body parts surgeries</li> </ul>

## 1.2 Problem Statement

In Malaysia, there were almost 20,000 patients undergo physiotherapy per hospital or rehab centre each year, incorporate with a multitude of disciplines of serious illness, such as stroke, Parkinson's, post – surgeries. This statistic was resulting in a large ratio of medical experts to patients with 1:600, respectively. Consequently, Malaysia aims to increase the number of physiotherapists to 19,000 by 2020 as to narrow down the ratio to 1:200 [4]. However, the need specialists in this sector are still high. Generally, patients need to be monitored while performing the movements so that the movements being executed correctly, and medical experts can track the progression. Nevertheless, the lack of experts make physiotherapy session delayed and cause discomfort to the patients and the caregivers as well.

On top of that, patients usually need to attend therapists at the clinic, and it is such a burden for the caregiver and the patients. It is so inconvenient for the patients, especially for elderly and bedridden patients, to travel back and forth once in a week for physiotherapy. Aside from that, patients may need to wear assistive devices such as sensors throughout the session. This leads to unpleasant training for patients. On the other hand, there are limited physical therapy equipment and also therapists allocated in a clinic or infirmary. Therefore, patients may have to wait longer to perform the exercises as the therapists are unable to assess them or the equipment is fully utilised by other patients.

There have been some significant attempts at engaging these problems such as the exploitation of serious games[5]–[9], wearable sensor technologies[5], [10]–[14], assistive technologies[15]–[19]. Those attempts were not wrong, but there is much room to improve. There is other revolutionary equipment that would help a rehab centre, physiotherapist or patient itself such as depth sensor camera which is low-cost and affordable for all the practitioners.

However, how far does this help the patients in knowing the progression?. The exercises somehow need to be monitored and assess in order to keep track of patients' progress. Physiotherapy assessment would help patients, as well as the experts in monitoring patients' progression towards a positive outcome. Hence, this study highlights the importance of the coalition between physical therapy and engineering; thus, the relationship can grow and fortify, allowing the technological developments to overcome the problems. The importance of the joint work between physiotherapists

and engineers will be demonstrated by the demands identified at the rehab centres. Technological advances for physiotherapy are developing increasingly, seeking a more efficient and targeted therapy to improve quality of life and social inclusion of people.

### 1.3 Research Aim

Hence, this is where technologies take place in assisting the experts conducting the session. Home rehabilitation seems to be the way out for the complications occur, which provides patients with a more flexible method to do the prescribed movements. This has caught the interest of many researchers concerning machine learning approaches to design a productive home rehabilitation exercise and classification method. Different machine learning algorithms have been utilised for recognizing different physiotherapy movements by recognising different parts of the body[20]. This study focuses on spike train feature extraction to achieve significant patterns and high data accuracy both on training and testing data. This thesis intends to improve physiotherapy assessment by providing quantitative data to the therapists, including movement correctness percentage to the patients themselves. These directions in future works are vast to enhance methods for the physiotherapy assessment system.

### 1.4 Research Objectives

Generally, the goal of the study is to develop a spike train feature extraction for application in rehabilitation movements' recognition and assessment limitations. Hence, the main objectives of this thesis are:

- i. To develop feature extraction algorithms based on spike train for physiotherapy movement recognition and assessment.
- ii. To determine the most optimum classifier based on the proposed framework for classifying the features with several CNN architectures.
- iii. To evaluate and validate the effectiveness of the proposed framework for rehabilitation movements' correctness predicted by deep learning approaches along with verification using Rehabilitation Movement Classification (REMOC).

## 1.5 Research Scopes

The details of the software tools, datasets, and performances measures are described as follows:

- i. This study covered the revolutionary technologies of physiotherapy sector over the period ranging from 2010 until 2020 across the world.
- ii. The study was evaluated among three datasets, which two of datasets are publicly available datasets, University of Idaho-Physical Rehabilitation Movement Data (UI-PRMD) and Kinect 3D active Dataset (K3Da). The other dataset is self-collected data developed in-house by Computer Networking Laboratory from Universiti Tun Hussein Onn Malaysia.
- iii. The data employed in this study only restricted to the extraction of raw data from a depth-sensor camera, Microsoft Kinect Xbox 360.
- iv. The exercises analysed in this study were chosen generally, which are not restricted to any illness, injuries, etc.
- v. There are seven performance measures adopted in this research, which are Mean Percentage Error (MPE) and Mean Absolute Deviation (MAD) utilised in movements correctness validation, the accuracy of recognition rate to measure the performance of the proposed CNN, and accuracy of correctness, precision, recall, and F1-Score to validate the physiotherapy assessment.
- vi. The software tools and design measurement for this research are as follows.
  - a. MATLAB is used to capture self-collected data, prepare for the data partition, spikes pattern generation, firing rates derivation, and CNN classification. All the graphs are plotted in MATLAB.
  - b. CNN simulation and training were run on a 2.5GHz Intel i5-3210M quad-core processor, 8GB RAM with Microsoft Windows.



## 1.6 Research Contributions

- i. This study proposed an advancement on the physiotherapy session system, which is a spike train as an extract feature for physiotherapy movement recognition and assessment. A significant spike pattern has been developed for each of an exercise by plotting spike trains into a raster plot. Hence, each of the exercises presents a unique pattern which can be differentiated visually and computationally.
- ii. Movements' correctness approach has been derived by estimating spike trains' firing rate in order to enhance the effectiveness of the self-physiotherapy session.
- iii. A proposed CNN framework has been developed and outperformed the other CNN architectures by achieving excellent accuracies for both recognition and prediction.
- iv. Proposed CNN framework is proven to successfully predict the correctness of movements as being compared to the MPE and MAD of average firing rates for a test and ground truth value. This proposed framework able to compete and achieve a significant result.
- v. This study is among the first successful attempts of implementing spike train into a deep learning framework for a real-time-based rehabilitation session case study with promising results.
- vi. Rehabilitation Movements' Classification, REMOC application has been developed entirely in MATLAB software, where it is a real-time physiotherapy session consisting of the movements' correctness and movements' classification features based on the proposed framework presented in this thesis.

## 1.7 Thesis Outlines

This thesis is organised into six chapters. Each of the chapters in the thesis was as follows:

i. Chapter 1: Introduction

In this chapter, this study briefly describes the background of the research, objectives, problem statements, scope of work, and contribution.

ii. Chapter 2: Literature Review

This chapter presents the review of current physiotherapy technologies and related works on the human activity recognition method by using a depth sensor camera, Microsoft Kinect. This chapter also briefly explain on spike train mechanism and its previous related work.

iii. Chapter 3: Research Methodology

This chapter covers the methodology taken to emphasize the contributions of the research work, algorithms, and implementation model of the proposed framework. This chapter also describes on UI-PRMD dataset, K3Da dataset, and self-collected dataset that being used for the experimental works.

iv. Chapter 4: Results and Discussion

This chapter discusses the overall experimental results for the proposed framework implemented to the datasets. Discussion and justification of the work are stated in this chapter.

v. Chapter 5: Application of spike train features in Rehabilitation Movement Classification (REMOC)

This chapter briefly introduced REMOC, Rehabilitation Movements Classification System. A system that was implementing the proposed framework to assist medical experts in managing patients for rehabilitation sessions.

vi. Chapter 6: Conclusion and Recommendation for Future Works

The final chapter summarises the thesis, re-stating the contributions and suggests ideas for future works, and concludes the overall research work.

## **CHAPTER 2**

### **LITERATURE REVIEW**

#### **2.1 Introduction**

Chapter 2 reflects the problems of physiotherapy assessment and examines the benefit of developing spike train features with deep learning approaches for this application. This chapter is written based on previous researchers' works and spike train development in various fields, including physiotherapy assessment. This study also discussed machine learning methods and compared to deep learning techniques with an overall objective of recognizing and assessing physiotherapy movements.

#### **2.2 Definition of physiotherapy**

Physiotherapy or Physical Therapy is a branch of health care that involves non-invasive methods of treatment and therapy for illnesses, weaknesses, and disabilities. This is a method of treatment that encompasses rehabilitation, injury prevention, healing, and promotion of holistic fitness. It focuses mainly on the movement science to resolve underlying physical issues caused by injury or disability and to help people recover, improve, and sustain the physical strength and energy. Using a variety of validated therapies and evidence-based natural approaches such as exercises and a range of massages, therapist experts help diagnose the condition and recommend a recovery plan that is ideally suited to enhance the physical well-being of the patients and to restore it to normality.

People seek physiotherapist to find lasting relief from the pain that could have been bothering for a prolonged period and restricting mobility due to several factors.

The pain and discomfort might be from injury, frozen shoulder, wrong posture, or any other external factor; the experts not only helps to relieve the pain but also recognise warning signs and prevent the pain from happening. Thus, regular physiotherapy can provide relief to people of all ages suffering from a variety of ailments, injuries, or disorders. Other benefits of physiotherapy include:

- i. Lasting relief from pain – There may be some aches and pains in the body for a variety of reasons, such as suffering from an ankle injury during sports activities or chronic low back pain due to long hours at work; it certainly demands urgent treatment if the pain affects daily tasks. Regular physiotherapy not only helps to minimize or even relieve discomfort but also minimize painkiller tolerance that is costly and dangerous in the long term.
- ii. Prevention from surgery – Although, sometimes, surgery may be necessary, physiotherapy may help altogether remove the need to go under the knife. The combination of exercises and rehabilitation with a range of medication helps remove pain from the root, heals damaged muscles, and promotes painless movement over some time. Nevertheless, if the patients already underwent surgery, physiotherapy helps in recovering and recuperating faster.
- iii. Improved mobility and balance – Patients who recover from an operation or injury usually take time to return to normal. Mobility can be a difficulty, and it is impossible to do daily tasks. Physiotherapy can be of great help in these situations. It helps not only the body to regain muscle strength but also agility to move around safely.
- iv. Manage age-related issues – As people ageing, people experience disorders of the bones, joints, or muscles such as osteoporosis and arthritis. Regular physiotherapy may be helpful in coping with these everyday issues and pains. It can also be preferred if a person had a knee and hip replacement surgery and looking for pain-reducing and heal faster.
- v. Avoid dependency on medicines – Although pain medication can provide immediate relief from pain, it can be fatal in the long run for kidneys and liver. Therefore, physiotherapy is considered a healthier and more effective to manage the pain for treating long-term pain issues.

Physiotherapy can be needed at any age, whether it is a toddler, a young adult, or a senior. If one suffered any form of sprain, muscle injury, or condition, physiotherapy could help improve one's overall physical well-being and heals faster. Some conditions that might be essential for people to seek for physiotherapy for long-term benefits as tabulated in Table 2.1. Experts basically assess one's condition, educate the person on the pain and its related issues as well as develop a rehabilitation program specifically suited for the condition. Hence, one's can lead a healthy, fit, and pain-free life.

Table 2.1: Experiences and conditions for a patient who seeks for physiotherapy

Experiences	Conditions
Posture problem	Back pain, lower back pain, neck pain, shoulder pain, muscle weakness, scapular instability, poor muscle tone, muscle imbalance, hypotonia
Joint pain	Arthritis, osteoporosis, poorly aligned joints, lupus, joint instability, bursitis, degenerative joints, age-related joint ailments
Joint injuries	Sprains & strains in ankle, knees, elbows, shoulder, wrist etc., torn cartilage, dislocated or unstable joints, degenerated meniscus, joint hypermobility
Recovery from surgery	Hip replacement, athletic injury surgery, tendon surgery, knee replacement, ligament surgery, spinal cord injury surgery, reconstructive surgery, lymph node replacement
Soft tissue injuries	Tennis elbow, golfers elbow, whiplash, Achilles tendinitis, back & neck strain, rotator cuff injuries, tendinitis
Bruising & Swelling	Bruising following sports or any other related injury or surgery, contusions, swollen joints, chronic joint or muscle inflammation, lymphedema, lymphatic congestion

Based on the patients' condition, the experts may prescribe a treatment plan taking into account one or a combination of a type of therapies, as in Table 2.2. Using a variety of hands-on therapies, including physical therapy, to stretch sore joints and muscles, therapeutic massages to relax tense muscles, machines, and devices to treat pain-related issues.

Table 2.2: Types of physiotherapy and its explanation

Physiotherapy	Explanation
Massage & Manipulation	By using the movement of hands, massage can manipulate the body's soft tissues. It is considered to be the most effective for treating pain, aches, & movement disorder in the neck, shoulder, and back area, curing headaches and stress-related issues.
Movement & Exercises	An efficient exercise plan is a significant aspect of physiotherapy that people are frequently encouraged to undergo when healing from an injury or attempting to strengthen their equilibrium or movement rate. These exercises strengthen the muscles and joints, improve control, and avoiding recurring injury. For example, for someone who had a stroke or facing paralysis, some specific exercises will be prescribed for the targeted area.
Energy-based Therapy	Often known as electrotherapy, various energies such as currents or pulses are used to activate the nervous system. The electrical pulses contract the muscles to ease out pain and stress from the body where leads to effective healing. It is a pain-free treatment but maybe tingled while undergoing them. The energy-based therapy are Ultrasound, Laser Therapy, Shortwave Diathermy, etc.
Hydrotherapy	It is a water-based therapy where it is carried out in the water. The temperature of the water is generally between hot and mild to help the muscles relax and alleviate pain. Hydrotherapy works as the weight of the water push against the body during the exercises. This helps to promote proper blood flow in the body and reduce pain.
Paediatric Physiotherapy	Its aim to at helping children with developmental issues and physical problems as patients may face movement difficulties due to a range of conditions such as Cerebral Palsy, Development Delay, Down's Syndrome,.
Neurological Physical Therapy	Patients with Alzheimer's, Parkinson's, or some other form of brain injury may have major positive effects on physical exercises. This can reduce the impact of neurological disorders from spreading all over the system and improve body movement and coordination
Cardiovascular Physical Therapy	If one is having heart issues or regulation of blood and oxygen, a cardiopulmonary physical therapy will help reduce complications such as heart attack and pulmonary fibrosis; increase strength in core muscles and boost long-term endurance

This study focused on movement and exercise physiotherapy, as it is the standard rehabilitation in most of the world. Movement and exercises can be done anywhere with space, whether in the rehab centre, home, or public park. By doing exercises, one could get rid of the pain, muscles, and joints stiffness that limit the movements to do daily tasks. In contrast, exercise may take a prolonged time for a patient to be back on track and recover full health. One need to do the exercises prescribed by the experts repeatedly until one are progressing in terms of speed and intensity.

## 2.3 Physiotherapy Assessment

The effectiveness of an exercise can be shown by measuring the progression of a patient that are regularly followed the prescribed exercise with the number of repetitions daily. The progression also may motivate patients by showing the improvement since rehab program started. There are different components of exercises that can be measured, as an example, the frequency of someone being active, the intensity of the activity, the type of activity engaged, and the duration of that activity. However, frequently, it is more practical to get an overall measurement of one's activity over a period.

Assessing the movements or exercises may increase to achieve the goal of improved health. However, there are several approaches to evaluating physiotherapy assessment in a rehabilitation centre. At a community level, good evaluations can lead to program improvements, documenting positive results can attract to continue and expand programs, and communicating results can persuade other communities to adopt practical approaches [21].

### 2.3.1 Conventional Physiotherapy Assessment

There are tons of rehabilitation centre has been built in this century. The rehabilitation centre helps patients with illnesses in order to cure the illness or to assist in daily activities. Each of the rehabilitation centres might have different approaches to physiotherapy assessment. Below is an example of approaches to measuring physiotherapy exercises that are used nowadays.

- i. Existing Records

This includes using information that is routinely collected, for example, census information, surveys from patients, or government data. However, sometimes the existing data does not meet the needs because of the broadness of the records, not focus on the specific targeted area, and outdated formatting that may have been gathered improperly.

- ii. Indirect Measures

Indirect measures basically rely on self-report. Patients need to estimate how much activity being done in a period. This approach can be useful because of



the minimal cost needed and easy to complete. However, the issues on relying on the recall may be appropriate for some older populations and people with dementia. Plus, there are other issues, such as dishonest, on telling the truth as to get a favourable result of the assessment.

### iii. Direct Measures

Direct measures use technology to measure activity levels, and this is usually as a device that measures and record movement. This might be a simple pedometer, an app on a smartphone, a sophisticated movement tracker, or a wearable sensor. This is the most used approach in many rehab centre as it is considered to be more accurate than self-report measures. However, the approach is costly and may not be appealing to some patients, e.g., the elders. Plus, the approach also has limitations, including:

- a. Inability to detect very minimal walking speeds.
- b. Inability to measure movement in abnormal gait patterns.
- c. Inability to gather data on certain types of activity, e.g., if a wearable sensor is placed on the lower limb, it is doubtful that the upper limb movement is observed. This concerns wheelchair users or someone who practices chair-based exercise.

Evaluation of physiotherapy assessment is challenging and often hindered by the challenge of employing an accurate and reliable measure that also adequately addresses the research problems [22]. Both indirect and direct measures contributed well to physiotherapy assessment; however, because of the barriers to accessing technology, indirect measures are still frequently adopted [23]. Despite the argument, direct measures appear to provide slightly more consistent results.

On the other hand, all three approaches explained are still valid and utilised in rehab centres. Figure 2.1 depicted the flow of a rehabilitation session in most of the centre. Each of the patients was prescribed the exercises based on the capabilities and conditions. In a session, patients were attached to the specific rehabilitation devices based on the illnesses. Throughout the session, the patient's performance data were interpreted to be evaluated by the medical experts and also will be stored for research. Once the performance has been evaluated, therapists will explain the feedback to the patients.






Figure 2.1: General flow of rehabilitation session in a rehabilitation centre

On the contrast, rehabilitation session in the centre is incompetent for bedridden patients or disabled patient as the needs to travel back and forth. Plus, the waiting game for a physiotherapists availability as well as the rehabilitation devices. The awful truth for most of the patients as the patients need to wait for the turns with an uncomfortable state. Therefore, this focused on a new direct measure for physiotherapy assessment, by utilising a 3D sensory camera, Kinect, which overcomes all the limitations mentioned.

## 2.4 Kinect-Based Physiotherapy Assessment

Virtual reality-based rehabilitation offers a highly interactive system with many documented benefits specifically to strokes patients [24], and a large variety have recently come to the forefront. Kinect is a 3D somatosensory camera that can input spontaneous data like human gestures, images, and voice etc. [25]. Patients or users can freely do the training without having to wear any sensors and also interact with the computer by making motions in front of Kinect. Kinect is beneficial to extinguish the space limits, and patients can manipulate with bare hands.

Furthermore, Kinect is a low-cost technology that makes its popularisation possible. With Kinect, people nowadays can execute training or rehabilitation exercises at home instead of frequently travel to the Rehabilitation Centre. The Kinect has been examined in healthcare to monitor and improve the process of physical

therapy and rehabilitation[26], [27]. Patients can now do home exercises and being monitored by Kinect. Correct adherence to supplemental home exercise is essential for safe, effective, and efficient rehabilitation care [28]. Table 2.3 summarizes the limitations of the approaches, as explained in the previous sub-section, and how the specification of Kinect overcome the limitations.

Table 2.3: Limitations of conventional approaches on physiotherapy assessment

Limitations	Solutions by Kinect's Features
Existing records are too broad and not targeted in a specific area	The programmatic gestures detection mainly tracking the position and movement of specific joints[29]–[31].
Dishonest, relying on recall of patients	Data from Kinect can be extracted out or be uploaded in Cloud[32]–[34].
Wearable sensors do not detect full-body movements when placed on a lower limb.	Kinect consists of 20 – 25 joints, where not even a single joint will be opted out despite any position of the patient was[11].
Inability to measure abnormal gestures	
Travel back and forth to rehab centre discomfort patients	Kinect is portable and can be implemented in-house so that patients can do home-based exercise monitored by Kinect[10], [11], [30], [35].
Waiting games in the rehab centres	Kinect basically can detect up to six people at a time [36], [37].

Until now, Microsoft Kinect, an active system for the assessment of human activity, has released two versions of Kinect Sensor, which Kinect v1 and Kinect v2. The Microsoft Kinect for Windows sensor v1 was launched in November 2010 while Kinect v2 was released just recently. Unlike contact sensors, Kinect is a non-contact sensor and is not wearable. It also does not require a battery replacement or charging port. Table 2.4 illustrates the technical specification for Kinect v1 and Kinect v2.

Table 2.4: Technical specification comparison of Kinect v1 and Kinect v2

Feature	Kinect v1	Kinect v2
Color Camera	640 x 480 @ 30 fps	1920 x 1080 @ 30 fps
Depth Camera	320 x 240	512 x 424
Max Depth Distance	~4.5 M	~4.5 M
Min Depth Distance	40 cm in near mode	50 cm
Horizontal Field of View	57 degrees	70 degrees
Vertical Field of View	43 degrees	60 degrees
Tilt Motor	Yes	No
Skeleton Joints Defined	20 joints	25 joints
Full Skeleton Tracked	2	6
USB Standard	2.0	3.0
Supported OS	Win 7, Win 8	Win 8

Recent studies have shown that Kinect Sensor can be used to quantify clinically relevant parameters of gait [38], [39], and posture [40]. Kinect-based virtual stepping therapy is effective for post-stroke rehabilitation of gait [41]. Boundless of applications and research on Kinect-based were conducted even now. The most leading applications on Kinect-based for rehabilitations exercises are Exercise Games and Serious Games.

Exercise games, known as exergames, intend to integrate natural human motion and entertainment in order to promote elderly exercise. In contrast, serious games aim to concurrently rehabilitate motor-impaired users and monitored patients' progress [42].

However, exercise games and serious games have to come to the limits as the requirements for clinical data capture for specific limb movements cannot be achieved. Below is the summarization of the limitations for exergames and serious games [42]:

- i. Designated games specifically for diagnostic usage are limited to non-occluding movements. This implies that standard stroke impairment level tests requiring extensive occluding movement sets may be untenable for a Kinect-based system to capture.

- ii. Diagnostic potential for extremities is limited to gross movements, as subtle movements of the hand and foot are currently outside the Kinect's capture sensitivity.
- iii. Games targeted at rehabilitation may be prone to "cheating," which means unnatural.
- iv. An appropriate response to failure and poor performance, if not accounted for during game design, can inherently limit positive outcomes due to demotivation.
- v. The benefits of the games mainly studied for short term and small-sized studies.

Besides, the games itself having cons as it is not suitable for all ages. For example, exergames and serious games are built only for young and middle ages people. It is inadequate for the elderly as the elderly might have secondary disabilities such as eyesight, hearing, speech problems; thus, it is inconvenient for the elder to focus on the screen as well as the games. The games were also irrelevant for bedridden patients. Hence, this study focuses on Kinect-based physiotherapy assessment as this system that combines optical- and radar-based technologies for human detection, tracking, and activity recognition.

Vision-based human action recognition is an orderly way to recognise and perceive the movement of people in camera-captured content. It composes of fields such as Biomechanics, Machine Vision, Image Processing, Artificial Intelligence, and Pattern Recognition [43]. Human activities can be classified into four categories, which are actions, gestures, interactions, and group activities [44]. Motion recognition composes of many actions such as walking, sitting, standing, running, waving. Figure 2.2 defines the steps in the human motion recognition system.




Figure 2.2: General framework of human action recognition

## 2.5 Human Detection

Human detection is an early stage for human action recognition. Detecting humans can be divided by many categories depends on human body parts such as an upper limb, lower limb, hands, arms, head, legs. Each of the body parts needs different detection methods to match the accuracy of the evaluation.

Computer vision and machine learning algorithms have been adopted to confront the problem of human detection in videos. There are many solutions and techniques introduced based on various scenarios, including variations in illumination and poses, as well as background clutter. Dalal & Triggs report impressive results on human detection [45] by implementing a Histogram of Gradient (HoG) as low-level features and outperformed other features such as wavelets[46], PCA-SIFT [47], and shape contexts[48]. Zhu et al. propose a rejection cascade using HoG features to improve the detection speed [49] while Zhang et al. come up with a multi-resolution framework in order to cut down computational cost[50].

In contrast, Lowe proposed the Scale-Invariant Feature Transform (SIFT), which has high accuracy and low computation time [51], which also being employed by Khaledian et al. for hand gesture recognition [52]. Ke and Sukthankar attempt to further improve the method by introducing PCA-SIFT [47]. Next, Speeded Up Robust Features by Bay et al. being introduced as it is shown to yield comparable or better results to SIFT[53].

Perhaps, the most recent, promising approach is detection by RGB-D cameras, such as the Kinect sensor. RGBD sensors are much more privacy-preserving than traditional video cameras because of human silhouette made it possible to achieve a higher level of privacy by only using a skeleton to represent a person[54]. This detection can be split into two standard methods, which are Depth Mapping and Skeletal Joints. The next sub-section discussed on related work for both depth maps and skeleton joints in physiotherapy-based. However, this study focused on exploiting skeleton joints data extracted from Kinect RGB-D sensors as the input for spike train analysis since skeletal data seems to promise and slightly better accurate than depth data in detecting physiotherapy movements [55], [56].



### 2.5.1 Depth Maps

Depth imaging technology has advanced adequately over the last few years, finally reaching a consumer price point with the launch of Kinect. Depth images provide depth information of an object or also known as z-information of an object in the real world. Depth maps can be collected through Stereo Camera, Laser Triangulation, etc. It is also widely used in many 3D vision algorithms recently.

The intensity values in an image represent the distance of the object from a viewpoint. As illustrated in Figure 2.3 a) there is a bottle and an umbrella in an area. The depth image in Figure 2.3 b) shows luminance in proportion to the distance of an object from the camera. The nearer object to the camera, which is the bottle, is darker while the further object, the umbrella, is lighter.




Figure 2.3: Comparison between normal and depth image using Kinect v2

In the last few years, solutions for activity recognition have been presented; the work intended to extract features from depth data such as [57], where the work is presenting the adaptive spatial-temporal pyramid to improving in retaining the spatial and temporal orders. Truong et al. developed a simple method from hand gesture recognition that achieve accurately in real-time using depth information from Kinect Sensor [58]. Author applying thresholds to the hand point that is tracked by the Bayesian Object Localisation method in the depth image to determine the hand region. Next, Samad et al. applied background segmentation with an improved adaptive Gaussian mixture algorithm to the depth map to detect moving objects [59].

Whereas the raw depth map has been smoothened by applying two filtering methods, which are pixel filtering and context filtering [60]. Then, the depth map is encoded through the proposed Local Ternary Direction Pattern (LTDP) feature



descriptor and utilised by the SVM classifier. The result turns out that LTDP outperformed the other five existing descriptors (LBP, LTP, HOG, PHOG, CENTRIST), and the nonlinear effect of the SVM classification task was reduced by using LTDP on the depth map.

Yang et al. proposed HOG in Depth Motion Maps (DMM-HOG), which applies the HOG descriptor on depth motion maps. It is computed by taking the difference of the depth maps in two consecutive frames, thresholding the difference, and aggregating the difference. Then, the work extract DMMs from the front, top, and side views [61]. Next, Xia et al. present a human detection method by depth information by Kinect, and the results can adequately detect the persons in all poses and appearances also provide an exact estimation of the whole-body contour of a person [62].

On the other hand, Ni et al. propose a method for action recognition by combining depth maps with RGB videos. The method is done by identifying the interest points in RGB videos, extracting HOG/HOF features, and LDP features from RGB videos and depth sequences, respectively, and concatenating the RGB and depth map features [63]. It shows that the information in RGB videos and depth map sequences are complementary to each other. There are extensive studies on depth images approaching rehabilitation, and physiotherapy assessment have been illustrated in Table 2.5.

Bakar et al. [64] and Sosa et al. [65] employs Region of Interest (ROI) in the segmentation phase to minimise the area and remove unwanted objects that appear around. Sinha et al. [66] proposed an algorithm in Depth-based segmentation and PCA to improve the accuracy of Kinect for upper body rehabilitation applications.

Next, Yao et al. [67] proposed a Kinect-based rehabilitation system for both therapists and patients. The work evaluates the time sequence-based data by implementing Cross-Correlation as the method is well known for detecting common periodicities. The work also employed DTW to compare whether the patients have done the exercises at the same rate as the skeleton frame sequences. It is to compare and find optimal alignment between two given time-sequences. Furthermore, Ye et al. [68] utilise DTW to compute a distance matrix for gait pattern extraction while Su et al. [35] applying DTW measure the similarity of joint data between "at home exercises" and "in hospital exercises."

Table 2.5: Kinect depth maps features for physiotherapy assessment

First author / Year	Health Disorder & Exercises	Dataset	Proposed Method	Limitations/ Strength
Y. J. Chang, 2013. [74]	Cerebral Palsy - Upper limb	Depth information	Kolmogorov-Smirnov Test	Only based on two CP cases.
B.Penelle, 2013. [75]	Lower limb	Depth images	GPU based Particle Filter	Robust to a certain degree of noise
S. Nomm, 2013. [69]	Motor Functions Therapeutic - Dynamic ROM	Depth information	NN-based ANARX	Complex as large number of parameters need to be identified
T. Watanabe, 2014. [76]	Elderly - toe lift, heel lift, Knee extensions	Depth Images -Seven subjects (75 – 85 yo)	Average Recognition Rate	Poor in joint positions' estimation
L. Yao, 2014. [67]	Rehabilitation Exercises	Depth Images	DTW	Only based on therapists' experience
C. J. Su, 2014. [35]	Post-injuries -Shoulder rehab exercises	Depth information	DTW Neural Network Fuzzy Logic	Model exercise are not generalised for all patients
M.Z. A. Bakar, 2015. [64]	Wrist Hand Injury -Hand Deviation	3D data Depth Data RGB Data	ROI Hand Contour K-Curvature	Limited data for validation
L. Omelina, 2016 [77]	Patients' recognition	Depth Images	LBP Chi-Square K-Mean	Discriminate between active and passive motion
G. D. Sosa, 2015. [65]	Multiple Sclerosis -shoulder elevation, abduction, hip abduction	RGB Data 2D with 30fps -Four subjects (24 – 39 yo)	ROI Background subtraction human silhouette skeletonisation	Only restricted for certain joints and front view measurement
S. Sinha, 2016. [66]	Upper Limb ROM exercise	RGB Depth -Ten subjects (21- 55yo)	PCA Proposed algorithm	Provide reliability for clinical assessment posture
M. Ye, 2017. [68]	Stroke -walking exercises	Depth map	DTW NARX Kernel Filter Enhanced RDF	Cost-effective, portable gait assessment system
D. Nahavandi, 2017. [70]	Musculoskeletal Disorder -Shoulder, Elbow, Trunk, Neck	Depth images -RULA Scoring	DCF Feature Extraction RDF	Only analyse static postures
J. Collins, 2017. [8]	Stroke - arm extensions, chest sway, waking	Depth data	HON4D	Ability to perform assessment on critical metrics
V. Nghia, 2017. [71]	Arm Flexion, Elevation, Abduction	Skeleton joint Depth images	Hand's Palm Status Detection	Low authentication

Su et al. then evaluate the performance by using the Adaptive Neuro-Fuzzy Inference System (ANFIS), which integrates a neural network and a fuzzy logic [35]. Nomm et al. practised Neural Network-based model, NN-based ANARX (Additive



Nonlinear Auto-Regressive exogenous), in the monitoring system as it can adjust the system according to the specific needs of each patient [69] whereas Ye et al. used NN-based on nonlinear autoregressive with exogenous (NARX) for gait phase classification and Enhanced Random Decision Forest (ERF) for missing features cases [68]. Next, Nahavandi et al. trained a Random Decision Forest (RDF) for generalising a learning model in order to discriminate between seven RULA-scored sets of postures [70].

In contrast, Collins et al. achieved to recognise several human actions by stroke patients with high certainty by employing HON4D as a global descriptor [8]. Nghia et al. proposed an algorithm to compute discriminative features, depth of wrist, by building a mapping table between the differences of joint bone depth and head depth as Kinect provided [71]. Consequently, depth maps are the right approach for detecting human action as it insensitive to changes in lighting conditions; hence it even works in low ambient light conditions [72]. Depth maps properties also convenience to works with specific feature descriptors, which spikes the evaluation performance [71], [73].

### 2.5.2 Skeleton Joints

Skeleton joints involve in combination number of joints that define body parts such as the head, shoulders, neck, and arms. This process describes a massive number of dimensions, and it describes unique individuals such as shapes, sizes, postures, motions. Each version of Kinect has a different number of joint types that made up a skeleton. For version 1 (Figure 2.4 (a)) comprises 20-joint types, while version 2 (Figure 2.4 (b)) comprises 25-joint types with additional five joints from Kinect v1. The new joints in Kinect v2 are Spineshoulder, HandTipLeft, ThumbLeft, HandTipRight, and ThumbRight. The details of each joint number have been explained in Table 2.6.

Skeleton Joints features are incompatible with working alone, as it is inadequate to identify various human actions. Hence, there are many developed methods of visual representations and machine learning methods in order to fully achieved skeleton features in human action recognition.

Raptis et al. successfully used skeleton positions in a real-time dance classification by employing Principal Component Analysis (PCA) on torso joints

positions. This is done to determine a human torso surface as well as defining a human pose with the spherical angles within the limb joint positions and torso surface [78]. Fourier transform is also being utilised over time to describe the temporal structure of actions.


Yang et al. proposed a new type of feature based on position differences between joints, Eigenjoint, to represent actions that combine action information [79]. The positions difference is extracted from all the pairs in one frame, the joint of continuing frames, and the joints of the initial frame with another frame to grab the structure of human postures. The work also applied PCA to the features to extract the crucial data for action recognition, "eigenjoints", then undergo action classification by applying nearest-neighbour classifier.

Xia et al. introduced an approach for human action recognition with a Histogram of 3D joint locations (HOJ3D). It extracts the histogram of spherical coordinates of the joint positions in a coordinates system that uses the hip joint as an origin [80]. The work also employed Shotton et al.'s method to extract 3D joint location from a depth image by employing a local mode-finding approach based on mean shift with a weighted Gaussian Kernel to compute the confidence-scored 3D position estimation of body joints [81].


Chaundry et al. illustrated the bio-inspired dynamic 3D discriminative skeleton feature by using linear dynamic systems to model the dynamic medial axis structures of human parts. The paper considered a discriminative metric to compare sets of linear dynamics systems for action recognition. Table 2.7 summarises relevant papers on Kinect based on physiotherapy and assessment using skeleton joints. Each paper proposed different methods for different rehabilitation exercises.

Janani et al. apply skeleton normalisation for pre-processing data to overcome discrepancies when a real-time quantitative assessment of exercises performed by TBI patients at home matched with the template exercises performed in the clinic [82] as well as in Jiang et al. [25], Lin et al. [83], Lee et al. [6], employ normalisation to compare and evaluate different skeleton models. In contrast, Cappecci et al. utilises Zero-Velocity Crossing (ZVC) to locate starting and ending points for human motion segmentation in order to identify moving points [84]. Han et al. scaling the values of joint points by implementing Z-Score Normalisation to improve the performance of a deep learning algorithm [85].

Further, on exercise assessment, Cappecci et al. [84] compared a Histogram Semi-Markov Model (HSMM) based algorithm to monitor and evaluate rehabilitation exercises with Dynamic Time Warping algorithm resulting HSMM outperformed DTW as HSMM demonstrated scores correlated better with the clinical scores. However, Janani et al. [82] stated that DTW surpasses the Direct Comparison and Cross-Correlation method as DTW able to give a significant score and achieve higher separation between most of the similar and dissimilar videos. DTW is also being used by Jiang et al. [25] and Anton et al. [86].



(a)



(b)

Figure 2.4: (a) 20-Joints of human body in action recognition through Kinect v1;  
(b) 25-Joints of human body in action recognition through Kinect v2

## REFERENCES

1. J. F. S. Lin, "Automated Rehabilitation Exercise Motion Tracking," University of Waterloo, 2012.
2. K. W. Loo and S. H. Gan, "Burden of Stroke in Malaysia," *Int. J. Stroke*, vol. 7, no. 2, pp. 165–167, 2012.
3. M. Kelly-Hayes, A. Beiser, C. S. Kase, A. Scaramucci, R. B. D'Agostino, and P. A. Wolf, "The influence of gender and age on disability following ischemic stroke: the Framingham study," *J. Stroke Cerebrovasc. Dis.*, vol. 12, no. 3, pp. 119–126, 2003.
4. H. Mahfoz, A. Ithnin, M. Rishnan, S. Siraj, and A. R. Zakaria, "Pola rekabentuk profesion fisioterapi masa depan dan impaknya kepada kurikulum sekolah menengah," 2014.
5. H. A. Meijer, M. Graafland, J. C. Goslings, and M. P. Schijven, "Systematic Review on the Effects of Serious Games and Wearable Technology Used in Rehabilitation of Patients With Traumatic Bone and Soft Tissue Injuries," *Archives of Physical Medicine and Rehabilitation*. 2018.
6. J. D. Lee, C. H. Hsieh, and T. Y. Lin, "A Kinect-based Tai Chi exercises evaluation system for physical rehabilitation," in *2014 IEEE International Conference on Consumer Electronics (ICCE)*, 2014, pp. 177–178.
7. O. Postolache, F. Cary, P. S. Girão, and N. Duarte, "Physiotherapy assessment based on Kinect and mobile APPs," in *2015 6th International Conference on Information, Intelligence, Systems and Applications (IISA)*, 2015, pp. 1–6.
8. J. Collins, J. Warren, M. Ma, R. Proffitt, and M. Skubic, "Stroke patient daily activity observation system," in *2017 IEEE International Conference on Bioinformatics and Biomedicine (BIBM)*, 2017, pp. 844–848.
9. C. L. Lai, Y. L. Huang, T. K. Liao, C. M. Tseng, Y. F. Chen, and D. Erdenetsogt, "A Microsoft Kinect-Based Virtual Rehabilitation System to Train Balance Ability for Stroke Patients," in *2015 International Conference*

on *Cyberworlds (CW)*, 2015, pp. 54–60.

10. W. Zhao and R. Lun, “A Kinect-based system for promoting healthier living at home,” in *2016 IEEE International Conference on Systems, Man, and Cybernetics (SMC)*, 2016, pp. 258–263.
11. G. Blumrosen, Y. Miron, N. Intrator, and M. Plotnik, “A Real-Time Kinect Signature-Based Patient Home Monitoring System,” *Sensors (Basel)*, vol. 16, no. 11, p. 1965, Nov. 2016.
12. G. Blumrosen, Y. Miron, M. Plotnik, and N. Intrator, “Towards a real time kinect signature based human activity assessment at home,” in *2015 IEEE 12th International Conference on Wearable and Implantable Body Sensor Networks (BSN)*, 2015, pp. 1–6.
13. Y. Liuy and L. Chengy, *Spiking-Neural-Network Based Fugl-Meyer Hand Gesture Recognition For Wearable Hand Rehabilitation Robot*. 2018.
14. D. R. F. Ordonez, “Deep convolutional and LSTM recurrent neural networks for multimodal wearable activity recognition,” *Sensors*, vol. 16, no. 1, p. 115, 2016.
15. S. Anton and F. D. Anton, “Monitoring rehabilitation exercises using MS Kinect,” in *2015 E-Health and Bioengineering Conference (EHB)*, 2015, pp. 1–4.
16. A. M. and S. B. and M. S. Foumani, “Accuracy of Kinect’s skeleton tracking for upper body rehabilitation applications,” *Disabil. Rehabil. Assist. Technol.*, vol. 9 4, no. 344–52, 2014.
17. J. Sung, C. Ponce, B. Selman, and A. Saxena, “Unstructured human activity detection from RGBD images,” in *2012 IEEE International Conference on Robotics and Automation*, 2012, pp. 842–849.
18. M. McNeill, D. Charles, J. Burke, J. Crosbie, and S. McDonough, “Evaluating user experiences in rehabilitation games,” *J Assist. Technol*, vol. 6, 2012.
19. A. P. L. Bo, M. Hayashibe, and P. Poignet, “Joint angle estimation in rehabilitation with inertial sensors and its integration with Kinect,” in *Proceedings of the Annual International Conference of the IEEE Engineering in Medicine and Biology Society, EMBS*, 2011.
20. Y. Liao, A. Vakanski, and M. Xian, “A Deep Learning Framework for Assessing Physical Rehabilitation Exercises,” *CoRR*, vol. abs/1901.1, 2019.
21. J. F. Sallis, “Measuring physical activity: practical approaches for program



PTTA UTM  
PERPUSTAKAAN TUNKU TUN MINAH

- evaluation in Native American communities,” *J. Public Health Manag. Pract.*, vol. 16, no. 5, pp. 404–410, 2010.
22. L. G. Sylvia, E. E. Bernstein, J. L. Hubbard, L. Keating, and E. J. Anderson, “Practical guide to measuring physical activity,” *J. Acad. Nutr. Diet.*, vol. 114, no. 2, pp. 199–208, Feb. 2014.
  23. S. Skender *et al.*, “Accelerometry and physical activity questionnaires - a systematic review,” *BMC Public Health*, vol. 16, no. 1, p. 515, 2016.
  24. G. Saposnik and M. Levin, “Virtual Reality in Stroke Rehabilitation,” *Stroke*, vol. 42, no. 5, pp. 1380–1386, 2011.
  25. X. Jiang, Huaqiang and Jie, “Kinect-Based Rehabilitation Training Assistant System Research And Implementation,” in *2013 International Conference on Software Engineering and Computer Science. Atlantis Press*, 2013.
  26. C. Y. Chang *et al.*, “Towards pervasive physical rehabilitation using Microsoft Kinect.” IEEE, USA, 2012.
  27. W. Zhao, R. Lun, D. Espy, and A. Reinthal, *Rule based realtime motion assessment for rehabilitation exercises*. 2014.
  28. D.Tino and C.Hillis, “The Full Can Exercise as the Recommended Exercise for Strengthening the Supraspinatus While Minimizing Impingement,” *Strength Cond. J.*, vol. 32, no. 5, pp. 33–35, 2010.
  29. Q. Wang, G. Kurillo, F. Ofli, and R. Bajcsy, “Evaluation of Pose Tracking Accuracy in the First and Second Generations of Microsoft Kinect,” in *2015 International Conference on Healthcare Informatics*, 2015, pp. 380–389.
  30. “Evaluating the microsoft kinect skeleton joint tracking as a tool for home-based physiotherapy ,” *Current Directions in Biomedical Engineering* , vol. 1. p. 184, 2015.
  31. B. B. Muhammad Latif Anjum, Stefano Rosa, “Tracking a Subset of Skeleton Joints: An Effective Approach towards Complex Human Activity Recognition,” *J. Robot.*, vol. 2017, 2017.
  32. M. Pirovano *et al.*, “Robust Silhouette Extraction from Kinect Data BT - Image Analysis and Processing – ICIAP 2013,” 2013, pp. 642–651.
  33. H. Kuang, S. Cai, X. Ma, and X. Liu, “An Effective Skeleton Extraction Method Based on Kinect Depth Image,” in *2018 10th International Conference on Measuring Technology and Mechatronics Automation (ICMTMA)*, 2018, pp. 187–190.



PT TAAUTHM  
PERPUSTAKAAN TUMAH



34. F. Centonze *et al.*, “Feature extraction using MS Kinect and data fusion in analysis of sleep disorders,” in *2015 International Workshop on Computational Intelligence for Multimedia Understanding (IWCIM)*, 2015, pp. 1–5.
35. C.-J. Su, C.-Y. Chiang, and J.-Y. Huang, “Kinect-enabled home-based rehabilitation system using Dynamic Time Warping and fuzzy logic,” *Appl. Soft Comput.*, vol. 22, pp. 652–666, 2014.
36. L. Cinque, A. Danani, P. Dondi, and L. Lombardi, “Real-Time Foreground Segmentation with Kinect Sensor BT - Image Analysis and Processing — ICIAP 2015,” 2015, pp. 56–65.
37. A. Farooq, A. Jalal, and S. Kamal, “Dense RGB-D Map-Based Human Tracking and Activity Recognition using Skin Joints Features and Self-Organizing Map,” *KSII Trans. Internet & Inf. Syst.*, vol. 9, no. 5, 2015.
38. E. E. Stone and M. Skubic, “Passive in-home measurement of stride-to-stride gait variability comparing vision and Kinect sensing,” in *2011 Annual International Conference of the IEEE Engineering in Medicine and Biology Society*, 2011, pp. 6491–6494.
39. R. A. Clark, K. J. Bower, B. F. Mentiplay, K. Paterson, and Y.-H. Pua, “Concurrent validity of the Microsoft Kinect for assessment of spatiotemporal gait variables,” *J. Biomech.*, vol. 46, no. 15, pp. 2722–2725, 2013.
40. R. A. Clark *et al.*, “Validity of the Microsoft Kinect for assessment of postural control,” *Gait Posture*, vol. 36, no. 3, pp. 372–377, 2012.
41. M. D. N. Roberto Lloréns, Mariano Alcañiz, Carolina Colomer Font, R. Lloréns, M. Alcañiz, C. Colomer, and M. D. Navarro, “Balance Recovery Through Virtual Stepping Exercises Using Kinect Skeleton Tracking: A Follow-Up Study With Chronic Stroke Patients,” *Stud. Health Technol. Inform.*, vol. 181, pp. 108–12, 2012.
42. D. Webster and O. Celik, “Systematic review of Kinect applications in elderly care and stroke rehabilitation,” *J. Neuroeng. Rehabil.*, vol. 11, no. 1, p. 108, Jul. 2014.
43. G. V. K. And and V. H. Patil, “A Study of Vision based Human Motion Recognition and Analysis,” *CoRR*, vol. abs/1608.0, 2016.
44. Jake K. Aggarwal and Michael S. Ryoo, “Human activity analysis: A review,” *ACM Comput. Surv.*, vol. 43, pp. 16:1–16:43, 2011.



45. N. Dalal and B. Triggs, "Histograms of oriented gradients for human detection," in *2005 IEEE Computer Society Conference on Computer Vision and Pattern Recognition (CVPR '05)*, 2005, vol. 1, pp. 886–893 vol. 1.
46. A. Mohan, C. Papageorgiou, and T. Poggio, "Example-based object detection in images by components," *IEEE Trans. Pattern Anal. Mach. Intell.*, vol. 23, no. 4, pp. 349–361, 2001.
47. Y. Ke and R. Sukthankar, "PCA-SIFT: a more distinctive representation for local image descriptors," in *Proceedings of the 2004 IEEE Computer Society Conference on Computer Vision and Pattern Recognition, 2004. CVPR 2004.*, 2004, vol. 2, pp. II-506-II-513 Vol.2.
48. S. Belongie, J. Malik, and J. Puzicha, "Shape matching and object recognition using shape contexts," *IEEE Trans. Pattern Anal. Mach. Intell.*, vol. 24, no. 4, pp. 509–522, 2002.
49. Q. Zhu, M.-C. Yeh, K.-T. Cheng, and S. Avidan, "Fast Human Detection Using a Cascade of Histograms of Oriented Gradients," in *2006 IEEE Computer Society Conference on Computer Vision and Pattern Recognition (CVPR '06)*, 2006, vol. 2, pp. 1491–1498.
50. W. Zhang, G. Zelinsky, and D. Samaras, "Real-time Accurate Object Detection using Multiple Resolutions," in *2007 IEEE 11th International Conference on Computer Vision*, 2007, pp. 1–8.
51. D. G. Lowe, "Distinctive Image Features from Scale-Invariant Keypoints," *Int. J. Comput. Vis.*, vol. 60, no. 2, pp. 91–110, 2004.
52. M. Khaledian and M. B. Menhaj, "Real-time vision-based hand gesture recognition using SIFT features," *Indones. J. Electr. Eng. Comput. Sci.*, vol. 15, no. 1, pp. 162–170, 2015.
53. H. Bay, T. Tuytelaars, and L. Van Gool, "SURF: Speeded Up Robust Features BT - Computer Vision – ECCV 2006," 2006, pp. 404–417.
54. J. R. Padilla-López, A. A. Chaaoui, F. Gu, and F. Flórez-Revuelta, "Visual privacy by context: proposal and evaluation of a level-based visualisation scheme," *Sensors*, vol. 15, no. 6, pp. 12959–12982, 2015.
55. E. Cippitelli, S. Gasparrini, E. Gambi, and S. Spinsante, "A Human Activity Recognition System Using Skeleton Data from RGBD Sensors," *Comput. Intell. Neurosci.*, vol. 2016, p. 4351435, 2016.
56. B. Hotrabhavananda, A. K. Mishra, M. Skubic, N. Hotrabhavananda, and C.





- Abbott, "Evaluation of the microsoft kinect skeletal versus depth data analysis for timed-up and go and figure of 8 walk tests," *Conf. Proc. ... Annu. Int. Conf. IEEE Eng. Med. Biol. Soc. IEEE Eng. Med. Biol. Soc. Annu. Conf.*, vol. 2016, pp. 2274–2277, Aug. 2016.
57. X. Yang and Y. Tian, "Super Normal Vector for Activity Recognition Using Depth Sequences," in *2014 IEEE Conference on Computer Vision and Pattern Recognition*, 2014, pp. 804–811.
  58. T. Q. Vinh and N. T. Tri, "Hand gesture recognition based on depth image using kinect sensor," in *2015 2nd National Foundation for Science and Technology Development Conference on Information and Computer Science (NICS)*, 2015, pp. 34–39.
  59. R. Samad, L. W. Yan, M. Mustafa, N. R. H. Abdullah, and D. Pebrianti, "Multiple Human Body Postures Detection using Kinect," *Indones. J. Electr. Eng. Comput. Sci.*, vol. 10, no. 2, 2018.
  60. Y. Shen, Z. Hao, P. Wang, S. Ma, and W. Liu, "A Novel Human Detection Approach Based on Depth Map via Kinect," in *2013 IEEE Conference on Computer Vision and Pattern Recognition Workshops*, 2013, pp. 535–541.
  61. X. Yang, C. Zhang, and Y. Tian, "Recognizing Actions Using Depth Motion Maps-based Histograms of Oriented Gradients," in *Proceedings of the 20th ACM International Conference on Multimedia*, 2012, pp. 1057–1060.
  62. L. Xia, C. C. Chen, and J. K. Aggarwal, "Human detection using depth information by Kinect," in *CVPR 2011 WORKSHOPS*, 2011, pp. 15–22.
  63. B. Ni, G. Wang, and P. Moulin, "RGBD-HuDaAct: A color-depth video database for human daily activity recognition," in *2011 IEEE International Conference on Computer Vision Workshops (ICCV Workshops)*, 2011, pp. 1147–1153.
  64. M. Z. A. Bakar, R. Samad, D. Pebrianti, M. Mustafa, and N. R. H. Abdullah, "Computer vision-based hand deviation exercise for rehabilitation," in *2015 IEEE International Conference on Control System, Computing and Engineering (ICCSCE)*, 2015, pp. 389–394.
  65. G. D. Sosa, J. Sánchez, and H. Franco, "Improved front-view tracking of human skeleton from Kinect data for rehabilitation support in Multiple Sclerosis," in *2015 20th Symposium on Signal Processing, Images and Computer Vision (STSIVA)*, 2015, pp. 1–7.

66. S. Sinha, B. Bhowmick, K. Chakravarty, A. Sinha, and A. Das, "Accurate upper body rehabilitation system using kinect," in *2016 38th Annual International Conference of the IEEE Engineering in Medicine and Biology Society (EMBC)*, 2016, pp. 4605–4609.
67. A. Yao, Li and Xu, Hui and Li, "Kinect-based rehabilitation exercises system: therapist involved approach," *Biomed. Mater. Eng.*, vol. 6, no. 24, pp. 2611–2618, 2014.
68. M. Ye, C. Yang, V. Stankovic, L. Stankovic, and S. Cheng, "Gait phase classification for in-home gait assessment," in *2017 IEEE International Conference on Multimedia and Expo (ICME)*, 2017, pp. 1524–1529.
69. Sven Nomm and Kirill Buhhalko, "Monitoring of the Human Motor Functions Rehabilitation by Neural Networks Based System with Kinect Sensor," in *IFAC HMS*, 2013.
70. D. Nahavandi and M. Hossny, "Skeleton-free task-specific rapid upper limb ergonomie assessment using depth imaging sensors," in *2016 IEEE SENSORS*, 2016, pp. 1–3.
71. T. T. N. Vo, A. T. Tran, V. H. Duong, J. C. Wang, and P. T. Bao, "Real time validating the accuracy of physiotherapy exercises," in *2017 IEEE International Conference on Consumer Electronics - Taiwan (ICCE-TW)*, 2017, pp. 329–330.
72. K. Rimkus, A. Bukis, A. Lipnickas, and S. Sinkevičius, "3D human hand motion recognition system," in *2013 6th International Conference on Human System Interactions (HSI)*, 2013, pp. 180–183.
73. S. Sinha, B. Bhowmick, A. Sinha, and A. Das, "Accurate estimation of joint motion trajectories for rehabilitation using Kinect," in *2017 39th Annual International Conference of the IEEE Engineering in Medicine and Biology Society (EMBC)*, 2017, pp. 3864–3867.
74. Y.-J. Chang, W.-Y. Han, and Y.-C. Tsai, "A Kinect-based upper limb rehabilitation system to assist people with cerebral palsy," *Res. Dev. Disabil.*, vol. 34, no. 11, pp. 3654–3659, 2013.
75. B. Penelle and O. Debeir, "Human motion tracking for rehabilitation using depth images and particle filter optimization," in *2013 2nd International Conference on Advances in Biomedical Engineering*, 2013, pp. 211–214.
76. T. Watanabe, N. Ohtsuka, S. Shibusawa, M. Kamada, and T. Yonekura,



- “Design of Lower Limb Chair Exercise Support System with Depth Sensor,” in *2014 IEEE 11th Intl Conf on Ubiquitous Intelligence and Computing and 2014 IEEE 11th Intl Conf on Autonomic and Trusted Computing and 2014 IEEE 14th Intl Conf on Scalable Computing and Communications and Its Associated Workshops*, 2014, pp. 104–111.
77. S. Lubos Omelina and Bart Jansen and Bruno Bonnechère and Milos Oravec and Jarmila Pavlovicova and {Van Sint Jan}, “Interaction detection with depth sensing and body tracking cameras in physical rehabilitation,” *Methods Inf. Med.*, vol. 55, no. 1, pp. 70–78, 2016.
  78. M. Raptis, D. Kirovski, and H. Hoppe, “Real-time Classification of Dance Gestures from Skeleton Animation,” in *Proceedings of the 2011 ACM SIGGRAPH/Eurographics Symposium on Computer Animation*, 2011, pp. 147–156.
  79. X. Yang and Y. L. Tian, “EigenJoints-based action recognition using Naïve-Bayes-Nearest-Neighbor,” in *2012 IEEE Computer Society Conference on Computer Vision and Pattern Recognition Workshops*, 2012, pp. 14–19.
  80. L. Xia, C. C. Chen, and J. K. Aggarwal, “View invariant human action recognition using histograms of 3D joints,” in *2012 IEEE Computer Society Conference on Computer Vision and Pattern Recognition Workshops*, 2012, pp. 20–27.
  81. J. Shotton *et al.*, “Real-time human pose recognition in parts from single depth images,” in *CVPR 2011*, 2011, pp. 1297–1304.
  82. J. Venugopalan, C. Cheng, T. H. Stokes, and M. D. Wang, “Kinect-based rehabilitation system for patients with traumatic brain injury,” in *2013 35th Annual International Conference of the IEEE Engineering in Medicine and Biology Society (EMBC)*, 2013, pp. 4625–4628.
  83. T. Y. Lin, C. H. Hsieh, and J. D. Lee, “A Kinect-Based System for Physical Rehabilitation: Utilizing Tai Chi Exercises to Improve Movement Disorders in Patients with Balance Ability,” in *2013 7th Asia Modelling Symposium*, 2013, pp. 149–153.
  84. M. Capecci *et al.*, “Physical rehabilitation exercises assessment based on Hidden Semi-Markov Model by Kinect v2,” in *2016 IEEE-EMBS International Conference on Biomedical and Health Informatics (BHI)*, 2016,



pp. 256–259.

85. S.-H. Han, H.-G. Kim, and H.-J. Choi, “Rehabilitation posture correction using deep neural network,” in *2017 IEEE International Conference on Big Data and Smart Computing (BigComp)*, 2017, pp. 400–402.
86. A. I. Antón, D., A. Goñi, “Exercise Recognition for Kinect-based Telerehabilitation,” *Methods Inf Med*, vol. 54, no. 2, 2015.
87. J. Richter, C. Wiede, B. Shinde, and G. Hirtz, “Motion Error Classification for Assisted Physical Therapy - A Novel Approach using Incremental Dynamic Time Warping and Normalised Hierarchical Skeleton Joint Data,” in *Proceedings of the 6th International Conference on Pattern Recognition Applications and Methods - Volume 1: ICPRAM*, 2017, pp. 281–288.
88. N. M. Khan, S. Lin, L. Guan, and B. Guo, “A Visual Evaluation Framework for In-Home Physical Rehabilitation,” in *2014 IEEE International Symposium on Multimedia*, 2014, pp. 237–240.
89. R. Staab, “Recognizing specific errors in human physical exercise performance with Microsoft Kinect,” *Master’s Theses Proj. Reports*, 2014.
90. R. Vemulapalli, F. Arrate, and R. Chellappa, “Human Action Recognition by Representing 3D Skeletons as Points in a Lie Group,” in *2014 IEEE Conference on Computer Vision and Pattern Recognition*, 2014, pp. 588–595.
91. R. Vemulapalli and R. Chellappa, “Rolling Rotations for Recognizing Human Actions from 3D Skeletal Data,” in *2016 IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, 2016, pp. 4471–4479.
92. Y. Du, W. Wang, and L. Wang, “Hierarchical recurrent neural network for skeleton based action recognition,” in *2015 IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, 2015, pp. 1110–1118.
93. V. Veeriah, N. Zhuang, and G. J. Qi, “Differential Recurrent Neural Networks for Action Recognition,” in *2015 IEEE International Conference on Computer Vision (ICCV)*, 2015, pp. 4041–4049.
94. W. Zhu *et al.*, “Co-occurrence Feature Learning for Skeleton based Action Recognition using Regularized Deep {LSTM} Networks,” *CoRR*, vol. abs/1603.0, 2016.
95. A. Shahroudy, J. Liu, T.-T. Ng, and G. Wang, “{NTU} {RGB+D:} {A} Large Scale Dataset for 3D Human Activity Analysis,” *CoRR*, vol. abs/1604.0, 2016.
96. J. Liu, A. Shahroudy, D. Xu, and G. Wang, “Spatio-Temporal {LSTM} with



- Trust Gates for 3D Human Action Recognition,” *CoRR*, vol. abs/1607.0, 2016.
97. M. Zanfir, M. Leordeanu, and C. Sminchisescu, “The Moving Pose: An Efficient 3D Kinematics Descriptor for Low-Latency Action Recognition and Detection,” in *2013 IEEE International Conference on Computer Vision*, 2013, pp. 2752–2759.
  98. M. A. Gouyayed *et al.*, “Histogram of Oriented Displacements (HOD): Describing Trajectories of Human Joints for Action Recognition,” in *CoRR*, 2013, vol. abs/1611.0, no. 7, pp. 2752–2759.
  99. S. Song, C. Lan, J. Xing, W. Zeng, and J. Liu, “An End-to-End Spatio-Temporal Attention Model for Human Action Recognition from Skeleton Data,” *CoRR*, vol. abs/1611.0, 2016.
  100. H. De Rosario, J. M. Belda-Lois, F. Fos, E. Medina, R. Poveda-Puente, and M. Kroll, “Correction of joint angles from kinect for balance exercising and assessment,” *J. Appl. Biomech.*, vol. 30, no. 2, pp. 294–299, 2014.
  101. S. Li, P. N. Pathirana, and T. Caelli, “Multi-kinect skeleton fusion for physical rehabilitation monitoring,” in *2014 36th Annual International Conference of the IEEE Engineering in Medicine and Biology Society*, 2014, pp. 5060–5063.
  102. Q. Wang, G. Kurillo, F. Ofli, and R. Bajcsy, “Remote Health Coaching System and Human Motion Data Analysis for Physical Therapy with Microsoft Kinect,” *CoRR*, vol. abs/1512.0, no. 1111965, 2015.
  103. T. Gollisch and M. Meister, “Rapid Neural Coding in the Retina with Relative Spike Latencies,” *Science*, vol. 319, pp. 1108–1111, Mar. 2008.
  104. R. Sinha, M. Hoon, J. Baudin, H. Okawa, R. O. L. Wong, and F. Rieke, “Cellular and Circuit Mechanisms Shaping the Perceptual Properties of the Primate Fovea,” *Cell*, vol. 168, no. 3, pp. 413–426.e12, Jan. 2017.
  105. J. D. Victor, “Spike train metrics,” *Curr. Opin. Neurobiol.*, vol. 15, no. 5, pp. 585–592, Oct. 2005.
  106. D. Butts *et al.*, “Temporal precision in the neural code and the timescales of natural vision,” *Nature*, vol. 449, pp. 92–95, Oct. 2007.
  107. P. Reinagel and R. C. Reid, “Temporal coding of visual information in the thalamus,” *J. Neurosci.*, vol. 20, no. 14, pp. 5392–5400, Jul. 2000.
  108. K. H. Srivastava *et al.*, “Motor control by precisely timed spike patterns,” *Proc. Natl. Acad. Sci. U. S. A.*, vol. 114, no. 5, pp. 1171–1176, Jan. 2017.
  109. C. Tang, D. Chehayeb, K. Srivastava, I. Nemenman, and S. J. Sober,



- “Millisecond-scale motor encoding in a cortical vocal area,” *PLoS Biol.*, vol. 12, no. 12, pp. e1002018–e1002018, Dec. 2014.
110. W. Gerstner and W. M. M., *Spiking Neuron Models: Single Neurons, Populations, Plasticity*. 2002.
  111. S. G. Wysoski, L. Benuskova, and N. Kasabov, “Fast and adaptive network of spiking neurons for multi-view visual pattern recognition,” *Neurocomputing*, vol. 71, no. 13, pp. 2563–2575, 2008.
  112. J. J. Wade, L. J. McDaid, J. A. Santos, and H. M. Sayers, “SWAT: a spiking neural network training algorithm for classification problems,” *IEEE Trans. neural networks*, vol. 21, no. 11, pp. 1817–1830, Nov. 2010.
  113. A. Tavanaei and A. S. Maida, “Training a Hidden Markov Model with a Bayesian Spiking Neural Network,” *CoRR*, vol. abs/1606.0, 2016.
  114. A. Tavanaei and A. S. Maida, “A spiking network that learns to extract spike signatures from speech signals,” *Neurocomputing*, vol. 240, pp. 191–199, 2017.
  115. P. B. S. G. S. C. A. . A. Khurshid, “Object and Character Recognition Using Spiking Neural Network,” in *Proceeding Materials Today*, 2018, vol. 5, no. 1, pp. 360–366.
  116. U. B. Rongala, A. Mazzoni, and C. M. Oddo, “Neuromorphic Artificial Touch for Categorization of Naturalistic Textures,” *IEEE Trans. Neural Networks Learn. Syst.*, vol. 28, no. 4, pp. 819–829, 2017.
  117. G. Spigler, C. M. Oddo, and M. C. Carrozza, “Soft-neuromorphic artificial touch for applications in neuro-robotics,” in *2012 4th IEEE RAS & EMBS International Conference on Biomedical Robotics and Biomechatronics (BioRob)*, 2012, pp. 1913–1918.
  118. N. Kasabov, K. Dhoble, N. Nuntalid, and G. Indiveri, “Dynamic evolving spiking neural networks for on-line spatio- and spectro-temporal pattern recognition,” *Neural Networks*, vol. 41, pp. 188–201, 2013.
  119. F. Ponulak and A. Kasiński, “Supervised Learning in Spiking Neural Networks with ReSuMe: Sequence Learning, Classification, and Spike Shifting,” *Neural Comput.*, vol. 22, no. 2, pp. 467–510, Oct. 2009.
  120. J. Storck, F. Jäkel, and G. Deco, “Temporal clustering with spiking neurons and dynamic synapses: Towards technological applications,” *Neural Netw.*, vol. 14, pp. 275–285, May 2001.
  121. S. Wysoski, L. Benuskova, and N. Kasabov, “Evolving spiking neural



- networks for audiovisual information processing,” *Neural Netw.*, vol. 23, pp. 819–835, Sep. 2010.
122. C. Panchev and S. Wermter, “Spike-timing-dependent synaptic plasticity: from single spikes to spike trains,” *Neurocomputing*, vol. 58–60, pp. 365–371, 2004.
  123. J. Wang, A. Belatreche, L. Maguire, and T. M. McGinnity, “An online supervised learning method for spiking neural networks with adaptive structure,” *Neurocomputing*, vol. 144, pp. 526–536, 2014.
  124. T. Masquelier and S. J. Thorpe, “Unsupervised Learning of Visual Features through Spike Timing Dependent Plasticity,” *PLOS Comput. Biol.*, vol. 3, no. 2, p. e31, Feb. 2007.
  125. A. Tavanaei, T. Masquelier, and A. S. Maida, “Acquisition of Visual Features Through Probabilistic Spike-Timing-Dependent Plasticity,” *CoRR*, vol. abs/1606.0, 2016.
  126. N. Kasabov *et al.*, “Evolving spiking neural networks for personalised modelling, classification and prediction of spatio-temporal patterns with a case study on stroke,” *Neurocomputing*, vol. 134, pp. 269–279, 2014.
  127. S. Ghosh-Dastidar and H. Adeli, “Improved spiking neural networks for EEG classification and epilepsy and seizure detection,” *Integr. Comput. Aided. Eng.*, vol. 14, pp. 187–212, Aug. 2007.
  128. Z. F. Mainen and T. J. Sejnowski, “Reliability of spike timing in neocortical neurons,” *Science*, vol. 268, no. 5216, pp. 1503–1506, Jun. 1995.
  129. W. Bair and C. Koch, “Temporal precision of spike trains in extrastriate cortex of the behaving macaque monkey,” *Neural Comput.*, vol. 8, no. 6, pp. 1185–1202, Aug. 1996.
  130. R. Herikstad, J. Baker, J.-P. Lachaux, C. M. Gray, and S.-C. Yen, “Natural Movies Evoke Spike Trains with Low Spike Time Variability in Cat Primary Visual Cortex,” *J. Neurosci.*, vol. 31, no. 44, pp. 15844 LP – 15860, Nov. 2011.
  131. J. Stone, *Principles of Neural Information Theory: Computational Neuroscience and Metabolic Efficiency*. 2018.
  132. P. A. Merolla *et al.*, “A million spiking-neuron integrated circuit with a scalable communication network and interface,” *Science (80-. )*, vol. 345, no. 6197, pp. 668 LP – 673, Aug. 2014.
  133. J. Seo *et al.*, “A 45nm CMOS neuromorphic chip with a scalable architecture for learning in networks of spiking neurons,” in *2011 IEEE Custom Integrated*



*Circuits Conference (CICC)*, 2011, pp. 1–4.

134. S. Carrillo *et al.*, “Advancing interconnect density for spiking neural network hardware implementations using traffic-aware adaptive network-on-chip routers,” *Neural Networks*, vol. 33, pp. 42–57, 2012.
135. [S. Carrillo *et al.*, “Scalable Hierarchical Network-on-Chip Architecture for Spiking Neural Network Hardware Implementations,” *IEEE Trans. Parallel Distrib. Syst.*, vol. 24, no. 12, pp. 2451–2461, 2013.
136. M. Vrigkas, C. Nikou, and I. A. Kakadiaris, “A Review of Human Activity Recognition Methods,” *Front. Robot. AI*, vol. 2, p. 28, 2015.
137. O. Oreifej and Z. Liu, “HON4D: Histogram of Oriented 4D Normals for Activity Recognition from Depth Sequences,” in *2013 IEEE Conference on Computer Vision and Pattern Recognition*, 2013, pp. 716–723.
138. A. Veenendaal, E. Daly, E. Jones, Z. Gang, S. Vartak, and R. S. Patwardhan, “Sensor Tracked Points and HMM Based Classifier for Human Action Recognition,” *Comput. Sci. Emerg. Res. J.*, vol. 5, 2016.
139. P. Afsar, P. Cortez, and H. Santos, “Automatic Human Action Recognition from Video Using Hidden Markov Model,” in *2015 IEEE 18th International Conference on Computational Science and Engineering*, 2015, pp. 105–109.
140. M. Z. Uddin and M. M. Hassan, “A depth video-based facial expression recognition system using radon transform, generalized discriminant analysis, and hidden Markov model,” *Multimed. Tools Appl.*, vol. 74, no. 11, pp. 3675–3690, Jun. 2015.
141. A. Mahapatra, T. K. Mishra, P. K. Sa, and B. Majhi, “Human recognition system for outdoor videos using Hidden Markov model,” *AEU - Int. J. Electron. Commun.*, vol. 68, no. 3, pp. 227–236, 2014.
142. M. Plappert, “Classification of Human Whole-Body Motion using Hidden Markov Models,” *CoRR*, vol. abs/1605.0, 2016.
143. M. Devanne, H. Wannous, S. Berretti, P. Pala, M. Daoudi, and A. Del Bimbo, “Space-Time Pose Representation for 3D Human Action Recognition BT - New Trends in Image Analysis and Processing – ICIAP 2013: ICIAP 2013 International Workshops, Naples, Italy, September 9-13, 2013. Proceedings,” A. Petrosino, L. Maddalena, and P. Pala, Eds. Berlin, Heidelberg: Springer Berlin Heidelberg, 2013, pp. 456–464.
144. A. Jalal, S. Kamal, and D. Kim, “Human Depth Sensors-Based Activity



PTIAUTHM  
PUSAT PENELITIAN TEKNOLOGI DAN INOVASI AKADEMIK



- Recognition Using Spatiotemporal Features and Hidden Markov Model for Smart Environments,” *J. Comput. Netw. Commun.*, vol. 2016, pp. 5--., Oct. 2016.
145. J. Deng, X. Xie, and B. Daubney, “A bag of words approach to subject specific 3D human pose interaction classification with random decision forests,” *Graph. Models*, vol. 76, no. 3, pp. 162–171, 2014.
  146. D. Pianu, R. Nerino, C. Ferraris, and A. Chimienti, “A novel approach to train random forests on GPU for computer vision applications using local features,” *Int. J. High Perform. Comput. Appl.*, vol. 30, no. 3, pp. 290–304, Dec. 2015.
  147. H. Rahmani, A. Mahmood, D. Q. Huynh, and A. Mian, “Real time action recognition using histograms of depth gradients and random decision forests,” in *IEEE Winter Conference on Applications of Computer Vision*, 2014, pp. 626–633.
  148. C. Lewis, “Written evidence (AIC0184). In Collated Written Evidence Volume: AI in the UK: ready, willing and able?, pp. 30-38, Select Committee on Artificial Intelligence, The Authority of the House of Lords,” 2018.
  149. A. L. Fogel and J. C. Kvedar, “Artificial intelligence powers digital medicine,” *npj Digit. Med.*, vol. 1, no. 1, p. 5, 2018.
  150. P. Lucas, “Bayesian analysis, pattern analysis, and data mining in health care,” *Curr. Opin. Crit. Care*, vol. 10, no. 5, pp. 399–403, 2004.
  151. M. Zhu, W. Chen, J. P. Hirdes, and P. Stolee, “The K-nearest neighbor algorithm predicted rehabilitation potential better than current Clinical Assessment Protocol,” *J. Clin. Epidemiol.*, vol. 60, no. 10, pp. 1015–1021, 2007.
  152. M. Zhu, Z. Zhang, J. P. Hirdes, and P. Stolee, “Using machine learning algorithms to guide rehabilitation planning for home care clients,” *BMC Med. Inform. Decis. Mak.*, vol. 7, p. 41, Dec. 2007.
  153. A. M. S. Muniz *et al.*, “Comparison among probabilistic neural network, support vector machine and logistic regression for evaluating the effect of subthalamic stimulation in Parkinson disease on ground reaction force during gait,” *J. Biomech.*, vol. 43, no. 4, pp. 720–726, 2010.
  154. O. Patsadu, C. Nukoolkit, and B. Watanapa, “Human gesture recognition using Kinect camera,” in *2012 Ninth International Conference on Computer Science and Software Engineering (JCSSE)*, 2012, pp. 28–32.



155. N. S. Suriani, "Fall Detection Using Visual Cortex Bio-inspired Model for Home-Based Physiotherapy System BT - Advances in Machine Learning and Signal Processing," 2016, pp. 47–57.
156. A. Jain, J. Tompson, Y. LeCun, and C. Bregler, "MoDeep: A Deep Learning Framework Using Motion Features for Human Pose Estimation BT - Computer Vision -- ACCV 2014," 2015, pp. 302–315.
157. J. Imran and P. Kumar, "Human action recognition using RGB-D sensor and deep convolutional neural networks," in *2016 International Conference on Advances in Computing, Communications and Informatics (ICACCI)*, 2016, pp. 144–148.
158. T. Pfister, J. Charles, and A. Zisserman, "Flowing ConvNets for Human Pose Estimation in Videos," *CoRR*, vol. abs/1506.0, 2015.
159. J. Mantyjarvi, J. Himberg, and T. Seppanen, "Recognizing human motion with multiple acceleration sensors," in *2001 IEEE International Conference on Systems, Man and Cybernetics. e-Systems and e-Man for Cybernetics in Cyberspace (Cat.No.01CH37236)*, 2001, vol. 2, pp. 747–752 vol.2.
160. N. Wang, E. Ambikairajah, N. H. Lovell, and B. G. Celler, "Accelerometry Based Classification of Walking Patterns Using Time-frequency Analysis," in *2007 29th Annual International Conference of the IEEE Engineering in Medicine and Biology Society*, 2007, pp. 4899–4902.
161. H. Lau, K. Tong, and H. Zhu, "Support vector machine for classification of walking conditions of persons after stroke with dropped foot.," *Hum. Mov. Sci.*, vol. 28, no. 4, pp. 504–514, Aug. 2009.
162. S. I. De Vries, F. G. Garre, L. H. Engbers, V. H. Hildebrandt, and S. Van Buuren, "Evaluation of neural networks to identify types of activity using accelerometers.," *Med. Sci. Sports Exerc.*, vol. 43, no. 1, pp. 101–107, Jan. 2011.
163. A. M. Khan, Y. Lee, S. Y. Lee, and T. Kim, "A Triaxial Accelerometer-Based Physical-Activity Recognition via Augmented-Signal Features and a Hierarchical Recognizer," *IEEE Trans. Inf. Technol. Biomed.*, vol. 14, no. 5, pp. 1166–1172, 2010.
164. O. D. Lara and M. A. Labrador, "A Survey on Human Activity Recognition using Wearable Sensors," *IEEE Commun. Surv. Tutorials*, vol. 15, no. 3, pp. 1192–1209, 2013.

165. I. Cuba Gyllensten and A. Bonomi, "Identifying Types of Physical Activity With a Single Accelerometer: Evaluating Laboratory-trained Algorithms in Daily Life," *IEEE Trans. Biomed. Eng.*, vol. 58, pp. 2656–2663, Jun. 2011.
166. Z. Wang, M. Jiang, Y. Hu, and H. Li, "An Incremental Learning Method Based on Probabilistic Neural Networks and Adjustable Fuzzy Clustering for Human Activity Recognition by Using Wearable Sensors," *IEEE Trans. Inf. Technol. Biomed.*, vol. 16, pp. 691–699, May 2012.
167. N. Lane and P. Georgiev, "Can Deep Learning Revolutionize Mobile Sensing?," pp. 117–122, Feb. 2015.
168. S. Mühlbacher-Karrer *et al.*, "A Driver State Detection System—Combining a Capacitive Hand Detection Sensor With Physiological Sensors," *IEEE Trans. Instrum. Meas.*, vol. 66, no. 4, pp. 624–636, 2017.
169. D. C. Ciresan, U. Meier, J. Masci, L. M. Gambardella, and J. Schmidhuber, "Flexible, High Performance Convolutional Neural Networks for Image Classification," in *Proceedings of the Twenty-Second International Joint Conference on Artificial Intelligence - Volume Volume Two*, 2011, pp. 1237–1242.
170. A. Toshev and C. Szegedy, "DeepPose: Human Pose Estimation via Deep Neural Networks," in *Proceedings of the 2014 IEEE Conference on Computer Vision and Pattern Recognition*, 2014, pp. 1653–1660.
171. J. A. Howe, E. L. Inness, A. Venturini, J. I. Williams, and M. C. Verrier, "The Community Balance and Mobility Scale - A balance measure for individuals with traumatic brain injury," *Clin. Rehabil.*, 2006.
172. G. Cook, L. Burton, B. J. Hoogenboom, and M. Voight, "Functional movement screening: the use of fundamental movements as an assessment of function - part 1.," *Int. J. Sports Phys. Ther.*, 2014.
173. J. W. Cuchna, M. C. Hoch, and J. M. Hoch, "The interrater and intrarater reliability of the functional movement screen: A systematic review with meta-analysis," *Physical Therapy in Sport*. 2016.
174. R. M. Hulteen, N. J. Lander, P. J. Morgan, L. M. Barnett, S. J. Robertson, and D. R. Lubans, "Validity and Reliability of Field-Based Measures for Assessing Movement Skill Competency in Lifelong Physical Activities: A Systematic Review," *Sports Medicine*. 2015.
175. E. D. Oña Simbaña, P. Sanchez-Herrera Baeza, A. Jardon Huete, and C.



PTTA UTM  
 PERPUSTAKAAN TEKNIK UNIVERSITI TEKNIKAL MELAKA

- Balaguer, "Review of automated systems for upper limbs functional assessment in neurorehabilitation," *IEEE Access*, 2019.
176. Y. Tao and H. Hu, "Colour based human motion tracking for home-based rehabilitation," in *Conference Proceedings - IEEE International Conference on Systems, Man and Cybernetics*, 2004.
  177. L. E. Sucar, F. Orihuela-Espina, R. L. Velazquez, D. J. Reinkensmeyer, R. Leder, and J. Hernandez-Franco, "Gesture therapy: An upper limb virtual reality-based motor rehabilitation platform," *IEEE Trans. Neural Syst. Rehabil. Eng.*, 2014.
  178. Y. Tao, H. Hu, W. Park, and U. Kingdom, "Building A Visual Tracking System for Home-Based," *Proc. 9th Chinese Autom. Comput. Soc. Conf. UK, Luton, Engl.*, 2003.
  179. M. Capecci *et al.*, "A tool for home-based rehabilitation allowing for clinical evaluation in a visual markerless scenario," in *Proceedings of the Annual International Conference of the IEEE Engineering in Medicine and Biology Society, EMBS*, 2015.
  180. M. Capecci *et al.*, "Accuracy evaluation of the Kinect v2 sensor during dynamic movements in a rehabilitation scenario," in *Proceedings of the Annual International Conference of the IEEE Engineering in Medicine and Biology Society, EMBS*, 2016.
  181. S. Spasojević, A. Rodić, and J. Santos-Victor, "Kinect-based approach for upper body movement assessment in stroke," in *Mechanisms and Machine Science*, 2019.
  182. T. Hachaj and M. R. Ogiela, "Rule-based approach to recognizing human body poses and gestures in real time," *Multimed. Syst.*, 2014.
  183. J. Y. Jung, J. I. Glasgow, and S. H. Scott, "Feature selection and classification for assessment of chronic stroke impairment," in *8th IEEE International Conference on BioInformatics and BioEngineering, BIBE 2008*, 2008.
  184. R. R. Coifman and S. Lafon, "Diffusion maps," *Appl. Comput. Harmon. Anal.*, 2006.
  185. A. Vakanski, J. M. Ferguson, and S. Lee, "Mathematical Modeling and Evaluation of Human Motions in Physical Therapy Using Mixture Density Neural Networks.," *J. Physiother. Phys. Rehabil.*, 2016.
  186. A. Paiement, L. Tao, S. Hannuna, M. Camplani, D. Damen, and M. Mirmehdi,



- “Online quality assessment of human movement from skeleton data,” in *BMVC 2014 - Proceedings of the British Machine Vision Conference 2014*, 2014.
187. L. Tao *et al.*, “A comparative study of pose representation and dynamics modelling for online motion quality assessment,” *Comput. Vis. Image Underst.*, 2016.
  188. F. Bashir, W. Qu, A. Khokhar, and D. Schonfeld, “HMM-based motion recognition system using segmented PCA,” in *Proceedings - International Conference on Image Processing, ICIP*, 2005.
  189. B. Crabbe, A. Paiement, S. Hannuna, and M. Mirmehdi, “Skeleton-Free Body Pose Estimation from Depth Images for Movement Analysis,” in *Proceedings of the IEEE International Conference on Computer Vision*, 2016.
  190. M. C. Huang, J. J. Liu, W. Xu, N. Alshurafa, X. Zhang, and M. Sarrafzadeh, “Using pressure map sequences for recognition of on bed rehabilitation exercises,” *IEEE J. Biomed. Heal. Informatics*, 2014.
  191. P. E. Taylor, G. J. M. Almeida, T. Kanade, and J. K. Hodgins, “Classifying human motion quality for knee osteoarthritis using accelerometers,” in *2010 Annual International Conference of the IEEE Engineering in Medicine and Biology Society, EMBC'10*, 2010.
  192. S. K. Jun, S. Kumar, X. Zhou, D. K. Ramsey, and V. N. Krovi, “Automation for individualization of Kinect-based quantitative progressive exercise regimen,” in *IEEE International Conference on Automation Science and Engineering*, 2013.
  193. Z. Zhang, Q. Fang, L. Wang, and P. Barrett, “Template matching based motion classification for unsupervised post-stroke rehabilitation,” in *Proceedings of 2011 International Symposium on Bioelectronics and Bioinformatics, ISBB 2011*, 2011.
  194. G. Kurillo, J. J. Han, A. Nicorici, and R. Bajcsy, “Tele-MFAsT: Kinect-based tele-medicine tool for remote motion and function assessment,” in *Studies in Health Technology and Informatics*, 2014.
  195. W. Zhao, R. Lun, D. D. Espy, and M. Ann Reinthal, “Realtime Motion Assessment For Rehabilitation Exercises: Integration Of Kinematic Modeling With Fuzzy Inference,” *J. Artif. Intell. Soft Comput. Res.*, 2015.
  196. F. Benettazzo *et al.*, “Low cost RGB-D vision based system to support motor disabilities rehabilitation at home,” *Biosyst. Biorobotics*, 2015.



PTTA UTHM  
PEPUSIAKAN TUN AMINAH



197. R. Houmanfar, M. Karg, and D. Kulic, "Movement Analysis of Rehabilitation Exercises: Distance Metrics for Measuring Patient Progress," *IEEE Syst. J.*, 2016.
198. R. Haghighi Osgouei, D. Soulsbv, and F. Bello, "An Objective Evaluation Method for Rehabilitation Exergames," in *2018 IEEE Games, Entertainment, Media Conference, GEM 2018*, 2018.
199. C.-J. Su, Á. Vieira, J. Mendes, C. Melo, and J. Machado, "Personal Rehabilitation Exercise Assistant with Kinect and Dynamic Time Warping," *Proc. Inst. Mech. Eng. Part H J. Eng. Med.*, vol. 3, pp. 448–454, Jan. 2013.
200. A. Vakanski, J. M Ferguson, and S. Lee, "Metrics for Performance Evaluation of Patient Exercises during Physical Therapy," *Int. J. Phys. Med. Rehabil.*, 2017.
201. J. Dorado *et al.*, "A computer-vision-based system for at-home rheumatoid arthritis rehabilitation," *Int. J. Distrib. Sens. Networks*, 2019.
202. M. Devanne and S. M. Nguyen, "Multi-level motion analysis for physical exercises assessment in kinaesthetic rehabilitation," in *IEEE-RAS International Conference on Humanoid Robots*, 2017.
203. M. Capecci *et al.*, "A Hidden Semi-Markov Model based approach for rehabilitation exercise assessment," *J. Biomed. Inform.*, 2018.
204. C. Williams, A. Vakanski, S. Lee, and D. Paul, "Assessment of physical rehabilitation movements through dimensionality reduction and statistical modeling," *Med. Eng. Phys.*, 2019.
205. M. Capecci *et al.*, "Physical rehabilitation exercises assessment based on Hidden Semi-Markov Model by Kinect v2," in *3rd IEEE EMBS International Conference on Biomedical and Health Informatics, BHI 2016*, 2016.
206. J. J. Hox and H. R. Boeije, "Data collection, primary versus secondary," 2005.
207. F. Han, B. Reily, W. Hoff, and H. Zhang, "Space-time representation of people based on 3D skeletal data: A review," *Comput. Vis. Image Underst.*, vol. 158, pp. 85–105, 2017.
208. F. De la Torre, J. Hodgins, J. Montano, and S. Valcarcel Macua, *Detailed Human Data Acquisition of Kitchen Activities: the CMU-Multimodal Activity Database (CMU-MMAC)*. 2009.
209. F. Ofli, R. Chaudhry, G. Kurillo, R. Vidal, and R. Bajcsy, "Berkeley MHAD: A comprehensive Multimodal Human Action Database," in *2013 IEEE*



- Workshop on Applications of Computer Vision (WACV)*, 2013, pp. 53–60.
210. J. Wang, Z. Liu, Y. Wu, and J. Yuan, “Mining actionlet ensemble for action recognition with depth cameras,” in *2012 IEEE Conference on Computer Vision and Pattern Recognition*, 2012, pp. 1290–1297.
  211. C. Chen, *UTD-MHAD: A Multimodal Dataset for Human Action Recognition Utilizing a Depth Camera and a Wearable Inertial Sensor*. 2015.
  212. L. Ar and Y. S. Akgul, “A computerized recognition system for the home-based physiotherapy exercises using an RGBD camera,” *IEEE Trans. neural Syst. Rehabil. Eng. a Publ. IEEE Eng. Med. Biol. Soc.*, vol. 22, no. 6, pp. 1160–1171, Nov. 2014.
  213. M. S. H. Aung *et al.*, “The Automatic Detection of Chronic Pain-Related Expression: Requirements, Challenges and the Multimodal EmoPain Dataset,” *IEEE Trans. Affect. Comput.*, vol. 7, no. 4, pp. 435–451, 2016.
  214. G. A. Nishiwaki, Y. Urabe, and K. Tanaka, “EMG Analysis of Lower Extremity Muscles in Three Different Squat Exercises,” *J. Japanese Phys. Ther. Assoc.*, vol. 9, no. 1, pp. 21–26, 2006.
  215. A. Reiss and D. Stricker, *Creating and Benchmarking a New Dataset for Physical Activity Monitoring*. 2012.
  216. A. Vakanski, H.-P. Jun, D. Paul, and R. Baker, “A Data Set of Human Body Movements for Physical Rehabilitation Exercises,” *Data*, vol. 3, no. 1, p. 2, Mar. 2018.
  217. D. Leightley, M. H. Yap, J. Piasecki, Y. Barnouin, and J. Mcphee, *Benchmarking Human Motion Analysis Using Kinect One: an open source dataset*. 2015.
  218. J. M. Guralnik *et al.*, “A short physical performance battery assessing lower extremity function: Association with self-reported disability and prediction of mortality and nursing home admission,” *J. Gerontol.*, vol. 49, no. 2, pp. M85–M9, 1994.
  219. D. Leightley, M. H. Yap, J. Piasecki, Y. Barnouin, and J. Mcphee, *Benchmarking Human Motion Analysis Using Kinect One: an open source dataset*. 2015.
  220. N. Salkind, “Encyclopedia of Research Design.” Thousand Oaks, California, 2010.
  221. J. F. Lin and D. Kulić, “Online Segmentation of Human Motion for Automated



- Rehabilitation Exercise Analysis,” *IEEE Trans. Neural Syst. Rehabil. Eng.*, vol. 22, no. 1, pp. 168–180, 2014.
222. R. Komatireddy, A. Chokshi, J. Basnett, M. Casale, D. Goble, and T. Shubert, “Quality and Quantity of Rehabilitation Exercises Delivered By A 3-D Motion Controlled Camera: A Pilot Study.,” *Int. J. Phys. Med. Rehabil.*, vol. 2, no. 4, Aug. 2014.
  223. T. Kreuz, J. S. Haas, A. Morelli, H. D. I. Abarbanel, and A. Politi, “Measuring spike train synchrony.,” *J. Neurosci. Methods*, vol. 165, no. 1, pp. 151–161, Sep. 2007.
  224. T. Kreuz, D. Chicharro, C. Houghton, R. G. Andrzejak, and F. Mormann, “Monitoring spike train synchrony.,” *J. Neurophysiol.*, vol. 109, no. 5, pp. 1457–1472, Mar. 2013.
  225. T. Kreuz, M. Mulansky, and N. Bozanic, “SPIKY: a graphical user interface for monitoring spike train synchrony,” *J. Neurophysiol.*, vol. 113, no. 9, pp. 3432–3445, May 2015.
  226. N. Milosevic, *Introduction to Convolutional Neural Networks*. 2020.
  227. A. Deshpande, “A Beginner’s Guide To Understanding Convolutional Neural Networks Part 1,” <https://adeshpande3.github.io/adeshpande3.github.io/A-Beginner%27s-Guide-To-Understanding-Convolutional-Neural-Networks/>, 2016. .
  228. A. Krizhevsky, I. Sutskever, and G. E. Hinton, “ImageNet Classification with Deep Convolutional Neural Networks,” in *Proceedings of the 25th International Conference on Neural Information Processing Systems - Volume 1*, 2012, pp. 1097–1105.
  229. C. Szegedy *et al.*, “Going Deeper with Convolutions,” *CoRR*, vol. abs/1409.4, 2014.
  230. K. He, X. Zhang, S. Ren, and J. Sun, “Deep Residual Learning for Image Recognition,” *CoRR*, vol. abs/1512.0, 2015.
  231. Z.-W. Yuan and J. Zhang, “Feature extraction and image retrieval based on AlexNet,” in *Eighth International Conference on Digital Image Processing (ICDIP 2016)*, 2016.
  232. S. Maudsley-Barton, J. McPhee, A. Bukowski, D. Leightley, and M. H. Yap, “A comparative study of the clinical use of motion analysis from kinect skeleton data,” in *2017 IEEE International Conference on Systems, Man, and*



*Cybernetics, SMC 2017*, 2017.

233. Y. Liao, A. Vakanski, and M. Xian, "A Deep Learning Framework for Assessing Physical Rehabilitation Exercises," *IEEE Trans. Neural Syst. Rehabil. Eng.*, 2020.
234. K. Polat, B. Akdemir, and S. Güneş, "Computer aided diagnosis of ECG data on the least square support vector machine," *Digit. Signal Process. A Rev. J.*, 2008.
235. M. D. McDonnell and N. G. Stocks, "Maximally informative stimuli and tuning curves for sigmoidal rate-coding neurons and populations," *Phys. Rev. Lett.*, 2008.
236. A. P. Nikitin, N. G. Stocks, R. P. Morse, and M. D. McDonnell, "Neural population coding is optimized by discrete tuning curves," *Phys. Rev. Lett.*, 2009.
237. S. Yaeli and R. Meir, "Error-based analysis of optimal tuning functions explains phenomena observed in sensory neurons," *Front. Comput. Neurosci.*, 2010.
238. M. L. Day, K. Koka, and B. Delgutte, "Neural encoding of sound source location in the presence of a concurrent, spatially separated source," *J. Neurophysiol.*, 2012.
239. "Advances in Neural Information Processing Systems," *Advances in Neural Information Processing Systems*. 2018.
240. F. Han, Z. Wang, H. Fan, and X. Sun, "Optimum neural tuning curves for information efficiency with rate coding and finite-time window," *Front. Comput. Neurosci.*, 2015.
241. S. Yarrow and P. Series, "The influence of population size, noise strength and behavioral task on Best-Encoded stimulus for neurons with unimodal or monotonic tuning curves," *Front. Comput. Neurosci.*, 2015.
242. W. B. Levy and R. A. Baxter, "Energy Efficient Neural Codes," *Neural Comput.*, 1996.
243. R. Wang and Z. Zhang, "Energy coding in biological neural networks," *Cogn. Neurodyn.*, 2007.
244. A. Moujahid, A. D'Anjou, F. J. Torrealdea, and F. Torrealdea, "Energy and information in Hodgkin-Huxley neurons," *Phys. Rev. E - Stat. Nonlinear, Soft Matter Phys.*, 2011.



PTTA UTHM  
PERPUSTAKAAN TUNKU TUN AMINAH

- 245. T. Berger and W. B. Levy, "A mathematical theory of energy efficient neural computation and communication," *IEEE Trans. Inf. Theory*, 2010.
- 246. B. Sengupta, S. B. Laughlin, and J. E. Niven, "Consequences of Converting Graded to Action Potentials upon Neural Information Coding and Energy Efficiency," *PLoS Comput. Biol.*, 2014.
- 247. L. Kostal and P. Lansky, "Information capacity and its approximations under metabolic cost in a simple homogeneous population of neurons," *BioSystems*, 2013.
- 248. P. Dayan and L. F. Abbott, *Theoretical Neuroscience: Computational and Mathematical Modeling of Neural Systems*. The MIT Press, 2005.



PTTA UTHM  
PERPUSTAKAAN TUNKU TUN AMINAH